



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

MODEL G0639 22-TON HYDRAULIC LOG SPLITTER

Product Dimensions:

Weight 560 lbs.
Overall Length/Width/(Raised Height), (Lowered Height)..... 88" x 40" x (71"), (45")

Shipping Dimensions:

Type Single Wood Crate
Content..... Single Unit
Length/Width/Height..... 74" x 19" x 17"

Engine Information:

Manufacturer Briggs & Stratton
Family..... 6BSXS.2051HC 276719
Model I/C6.5 Industrial/Commercial
Cylinder Type..... Dura-Bore Cast Iron Sleeve
Main Bearing Type..... Dual Ball Bearing
Valve Style Overhead
Cylinders Single
Cylinder Head Hi-Flow
Displacement 206 cc, 12.57 cubic in.
Bore..... 2.69 cu/in
Stroke 2.20 in
Oil Capacity (Shipped Empty)..... 20 Oz
Fuel Capacity (Shipped Empty) 1 Gallon
Air Cleaner High Capacity Dual-Clean
Lubrication..... Splash Lubrication
Shipped with Oil No
Ignition..... Magnatron
Governor Mechanical
Muffler Lo-Tone
Fuel Shutoff Valve..... Yes
Weight 34 lbs.

Hydraulic Information:

Maximum Pump Pressure..... 3000 PSI
Maximum Pump Flow 8 GPM
Hydraulic Fluid Capacity (Shipped Empty) 2.5 Gallons
Hydraulic Fluid Type 10W AW32, ASLE H-150, or ISO32
Pump Pressure Relief Setting..... 3000 PSI
Hydraulic Cylinder Bore 4" Dia
Hydraulic Cylinder Stroke 24"
Control Valve/Cylinder Operation Power Splitting, Neutral, and Power Retracting
Filter Type Reusable Tank Screen
Tank Type Vented



Chassis:

Type All Steel
Tow Ball Receiver 2"
Wheels and Tires Steel and Tubeless Tires (4.80/4.00-8)
Wheel Bearing Type Bushing
Towing Conditions Not Street Legal, Under 12 MPH, Off Road Only

Other Specifications:

Country Of Origin China
Warranty..... 1 Year
Serial Number Location ID Label on Hydraulic Cylinder
Assembly Time 1.5 Hrs.

Features:

- Heavy Duty Construction
- Power Splitter Retract
- 24" Splitting Stroke
- 22-Ton Splitter Load

