MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0679 6" X 186" STROKE SANDER

Product Dimensions:

Weight..... 608 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 98 x 47-5/8 x 67-1/2 in.
Footprint (Length x Width)..... 69-1/4 x 31 in.

Shipping Dimensions:

Type..... Wood Crate
Content..... Machine
Weight..... 744 lbs.
Length x Width x Height..... 36 x 87 x 23 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 17A
Minimum Circuit Size..... 30A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 14 AWG
Plug Included..... No
Recommended Plug Type..... L6-30
Switch Type..... Magnetic Switch w/Overload Protection

Motors:

Main

Horsepower..... 3 HP
Phase..... Single-Phase
Amps..... 17A
Speed..... 1750 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer ..... Direct Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Operation Information

Sanding Belt Speed..... 3600 FPM
Sanding Belt Length..... 186 in.
Sanding Belt Width..... 6 in.

Table Information

Table Length..... 59 in.
Table Width..... 23-3/4 in.
Table Thickness..... 3 in.
Table Travel..... 18 in.
Floor To Table Height..... 21-3/8 – 42-3/4 in.

The information contained herein is deemed accurate as of 4/17/2024 and represents our most recent product specifications. Due to our ongoing improvement efforts, this information may not accurately describe items previously purchased.

Platen Information

Platen Type..... Graphite Coated
Platen Length..... 6 in. x 10-1/2 in. (Movable)
Platen Width..... 6 in.
Platen Travel..... 50-1/2 in.

Construction

Table..... Steel w/Composite Wood Top
Frame..... Steel
Base..... Steel
Drive Roller..... Aluminum
Paint Type/Finish..... Powder Coated

Other Related Information

Number of Dust Ports..... 2
Dust Port Size..... 4 in.

Other Specifications:

Country of Origin ..... Taiwan
Warranty ..... 1 Year
Approximate Assembly & Setup Time ..... 3 Hours
Serial Number Location ..... ID Label on Front of Machine
ISO 9001 Factory ..... Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) ..... No

Features:

21 In. Maximum Workpiece Thickness
Horizontal Belt Position for Stroke Sanding and Vertical Belt Position for Edge Sanding
Sliding Ways Travel on Ball Bearings
Fully Adjustable Belt Tracking and Tension
Motor Brake Quickly Stops Belt Movement

The information contained herein is deemed accurate as of 4/17/2024 and represents our most recent product specifications. Due to our ongoing improvement efforts, this information may not accurately describe items previously purchased.