



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0702 12" DISC SANDER W/ BRAKE

Product Dimensions:

Weight..... 84 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 16-1/2 x 27 x 17 in.
Footprint (Length x Width)..... 16-1/2 x 16-1/2 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 92 lbs.
Length x Width x Height..... 19 x 26 x 17 in.

Electrical:

Power Requirement..... 120V, Single-Phase, 60 Hz
Prewired Voltage..... 120V
Full-Load Current Rating..... 9.5A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 5 ft.
Power Cord Gauge..... 16 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Paddle Safety Switch w/Removable Key

Motors:

Main

Horsepower..... 1 HP
Phase..... Single-Phase
Amps..... 9.5A
Speed..... 1720 RPM
Type..... TEFC Capacitor-Start Induction w/Brake
Power Transfer..... Direct Drive
Bearings..... Sealed & Permanently Lubricated

Main Specifications:

Disc Sander Info

Disc Diameter..... 12 in.
Disc Speed..... 1720 RPM
Disc Sandpaper Backing Type..... PSA
Table Tilt..... Left 15, Right 45 deg.
Table-to-Floor Height..... 9-1/2 in.

Construction Materials

Base..... Steel
Table..... Cast Iron
Disc..... Cast Iron
Miter Gauge..... Plastic/Aluminum Bar

Other Related Info

Miter Gauge Slot Width..... 5/8 in.
Miter Gauge Slot Height..... 3/16 in.

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 30 Minutes
ISO 9001 Factory No
Certified by a Nationally Recognized Testing Laboratory (NRTL) Yes

Features:

Table Tilt Range Left 15, Right 45 Deg.
Accepts 12 In. PSA Discs
Large Tilting Precision-Ground Cast-Iron Table
X- and Y-Axis Slots
Steel Base