



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0719 15" DISC SANDER WITH STAND

Product Dimensions:

Weight..... 201 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 20-1/2 x 26 x 46 in.
Footprint (Length x Width)..... 20-1/2 x 26 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard Box
Content..... Machine
Weight..... 149 lbs.
Length x Width x Height..... 25 x 22 x 20 in.

Carton #2

Type..... Cardboard Box
Content..... Cabinet Stand
Weight..... 72 lbs.
Length x Width x Height..... 29 x 23 x 11 in.

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
Full-Load Current Rating..... 12A
Minimum Circuit Size..... 15A
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 14 AWG
Plug Included..... Yes
Included Plug Type..... NEMA 6-15
Switch Type..... Paddle Switch w/Disabling Key

Motors:

Main

Horsepower..... 1-1/2 HP
Phase..... Single-Phase
Amps..... 12A
Speed..... 1725 RPM
Type..... TEFC Capacitor Start w/Brake, 220V
Power Transfer Direct Drive
Bearings..... Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Disc Sander Info

Disc Diameter.....	15 in.
Disc Speed.....	1725 RPM
Disc Sandpaper Backing Type.....	PSA
Table Length.....	20 in.
Table Width.....	12 in.
Table Thickness.....	9/16 in.
Table Tilt.....	Left 15, Right 45 deg.
Table-to-Floor Height.....	37 in.

Construction Materials

Base.....	Steel
Stand.....	Steel
Table.....	Precision Ground Cast Iron
Disc.....	Cast Iron
Miter Gauge.....	Aluminum
Paint Type/Finish.....	Powder Coated

Other Related Info

Miter Gauge Slot Width.....	3/4 in.
Miter Gauge Slot Height.....	5/16 in.
Number of Dust Ports.....	1
Dust Port Size.....	2-1/2 in.
Compatible Mobile Base.....	D2057A

Other Specifications:

Country of Origin	Taiwan
Warranty	1 Year
Approximate Assembly & Setup Time	30 mins
Serial Number Location	ID Label on Cabinet
Sound Rating	75 dB
ISO 9001 Factory	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL)	No

Features:

- Automatic internal motor braking system
- Table tilt range +15 deg. to -45 deg.
- Accepts 15" PSA discs
- Large tilting precision-ground cast-iron table
- X- and Y-axis miter slots
- Steel base