



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0732 CONTRACTOR STYLE SAW

### Product Dimensions:

Weight..... 198 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 54-3/4 x 38-1/4 x 43 in.  
Footprint (Length x Width)..... 28 x 28 in.

### Shipping Dimensions:

Type..... Cardboard Box  
Content..... Machine  
Weight..... 208 lbs.  
Length x Width x Height..... 36 x 28 x 18 in.

### Electrical:

Power Requirement..... 110V or 220V, Single-Phase, 60 Hz  
Prewired Voltage..... 110V  
Full-Load Current Rating..... 11.5A at 110V, 5.7A at 220V  
Minimum Circuit Size..... 15A at 110V, 15A at 220V  
Connection Type..... Cord & Plug  
Power Cord Included..... Yes  
Power Cord Length..... 6 ft.  
Power Cord Gauge..... 14 AWG  
Plug Included..... Yes  
Included Plug Type..... 5-15 for 110V  
Recommended Plug Type..... 6-15 for 220V  
Switch Type..... Paddle Safety Switch w/Removable Key

### Motors:

#### Main

Horsepower..... 1.5 HP  
Phase..... Single-Phase  
Amps..... 11.5A /5.7A  
Speed..... 3600 RPM  
Type..... TEFC Capacitor-Start Induction  
Power Transfer ..... Belt Drive  
Bearings..... Shielded & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... External

### Main Specifications:

#### Main Information

Table Saw Type..... Contractor  
Maximum Blade Diameter..... 10 in.  
Arbor Size..... 5/8 in.  
Arbor Speed..... 4000 RPM  
Maximum Width of Dado..... 13/16 in.  
Blade Tilt Direction..... Left  
Max Blade Tilt..... 45 deg.  
Maximum Depth of Cut At 90 Degrees..... 3-1/8 in.  
Maximum Depth of Cut At 45 Degrees..... 2-1/4 in.  
Max Rip Right of Blade w/Included Fence & Rails..... 30 in.  
Max Rip Left of Blade w/Included Fence & Rails..... 12 in.

**Additional Blade Information**

Included Blade Information.....	10" x 40T
Riving Knife/Spreader Thickness.....	0.090 in.
Required Blade Body Thickness.....	0.078 in.
Required Blade Kerf Thickness.....	0.118 in.
Rim Speed at Max Blade Diameter.....	10,500 FPM

**Table Information**

Floor to Table Height.....	36-1/2 in.
Table Size with Extension Wings Width.....	40 in.
Table Size with Extension Wings Depth.....	25-1/4 in.
Distance Front of Table to Center of Blade.....	13-1/2 in.
Distance Front of Table to Blade At Maximum Cut.....	8-7/8 in.
Main Table Size Thickness.....	1-1/2 in.

**Fence Information**

Fence Type.....	Camlock T-Shape w/Aluminum Face
Fence Size Length.....	28 in.
Fence Size Width.....	1-5/8 in.
Fence Size Height.....	2-1/4 in.
Fence Rail Type.....	Extruded Aluminum
Fence Rail Length.....	54-3/4 in.
Fence Rail Width.....	2-3/4 in.
Fence Rail Height.....	1-3/4 in.

**Miter Gauge Information**

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Miter Gauge Slot Size Height.....	3/8 in.

**Construction**

Table.....	Precision-Ground Cast Iron
Wings.....	Sheet Metal
Trunnions.....	Cast Iron
Body Assembly.....	Pre-Formed Steel
Fence Assembly.....	Steel and Aluminum
Rails.....	Extruded Aluminum
Miter Gauge Construction.....	Aluminum
Guard.....	Steel and Clear Plastic
Body/Cabinet Paint Type/Finish.....	Powder Coated
Arbor Bearings.....	Sealed & Permanently Lubricated

**Other Related Information**

Number of Dust Ports.....	1
Dust Port Size.....	2-1/2 in.
Compatible Mobile Base.....	D2057A

**Other Specifications:**

Country of Origin .....	Taiwan
Warranty .....	1 Year
Approximate Assembly & Setup Time .....	1 Hour
Serial Number Location .....	ID Label on Front of Cabinet
Sound Rating .....	95 dB
ISO 9001 Factory .....	No
Certified by a Nationally Recognized Testing Laboratory (NRTL) .....	Yes

**Features:**

- Quick-Release Blade Guard and Spreader
- Clear plastic guard with splitter
- Riving knife
- Quick Release Riving Knife
- Enclosed Motor Cover
- 2-1/2" Dust Port
- Aluminum Miter Gauge
- Cogged V-Belt
- Precision-Ground Cast-Iron Table and Sheet Metal Wings
- Aluminum and Steel Rails
- Powder Coated Paint
- Extruded Aluminum Camlock fence with Micro-Adjust Feature
- Align-A-Cut Marker for Easily Aligning Workpiece Outline with Blade
- Encapsulated Blade Assembly for Efficient Dust Extraction
- Rail-Mounted Switch
- Zero-Clearance Table Insert Included
- Included Push Stick
- Included 10" x 40T Carbide-Tipped Blade

**Accessories Recommended:**

- G7582 Master Plate
- G7581 SuperBar
- D2057A Heavy-Duty Mobile Base
- H8029 5 pc. Safety Kit