



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0739 1/2 HP BENCHTOP OSCILLATING SPINDLE SANDER

### Product Dimensions:

Weight..... 30 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 15-9/16 x 14-1/8 x 17 in.  
Footprint (Length x Width)..... 15-1/2 x 14 in.

### Shipping Dimensions:

Type..... Cardboard Box  
Content..... Machine  
Weight..... 33 lbs.  
Length x Width x Height..... 19 x 16 x 20 in.  
Must Ship Upright..... No

### Electrical:

Power Requirement..... 120V, Single-Phase, 60 Hz  
Prewired Voltage..... 120V  
Full-Load Current Rating..... 3.5A  
Minimum Circuit Size..... 15A  
Connection Type..... Cord & Plug  
Power Cord Included..... Yes  
Power Cord Length..... 6 ft.  
Power Cord Gauge..... 18 AWG  
Plug Included..... Yes  
Included Plug Type..... 1-15  
Switch Type..... Paddle Safety Switch w/Removable Key

### Motors:

#### Main

Horsepower..... 1/2 HP  
Phase..... Single-Phase  
Amps..... 3.5A  
Type..... Permanent Magnet Motor  
Power Transfer ..... V-Belt Drive  
Bearings..... Sealed & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... N/A

### Main Specifications:

**Spindle Sander Info**

Sanding Drum Diameters.....	1/2, 3/4, 1, 1-1/2, 2, 3 in.
Sanding Drum Length.....	4-1/2 in.
Spindle Speed.....	2000 RPM
Spindle Oscillation.....	58 SPM
Stroke Length.....	5/8 in.
Table Length.....	15 in.
Table Width.....	11-1/2 in.
Table Thickness.....	1-5/16 in.
Table-to-Floor Height.....	13 in.
Spindle Shaft Diameter.....	1/2 in.
Number of Table Inserts.....	6
Included Sanding Sleeve Grit Size.....	80

**Construction Materials**

Base.....	Plastic
Table.....	Cast Iron

**Other Related Info**

Number of Dust Ports.....	1
Dust Port Size.....	1-1/2 in.

**Features:**

- Space-saving benchtop style.
- Sanding drums store neatly in the base for easy, organized access.
- Includes 3 spindle washers: 5/8, 7/8, 1-3/4 in.
- Includes 6 table inserts: 1/2, 3/4, 1, 1-1/2, 2, 3 in.
- Includes 6 sanding sleeves: 1/2, 3/4, 1, 1-1/2, 2, 3 in.
- Includes 5 rubber sanding spindles: 3/4, 1, 1-1/2, 2, 3 in.