



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0767 ABRASIVE TUBE NOTCHER

Product Dimensions:

Weight 290 lbs.
Width (side-to-side) x Depth (front-to-back) x Height 31-1/2" x 49-1/4" x 47-1/4"
Foot Print (Length/Width)..... 25-1/2" x 15-3/4"

Shipping Dimensions:

Type Wood Crate
Weight 381 lbs.
Length/Width/Height..... 48" x 28" x 45"
Must Ship Upright Yes

Electrical:

Required Requirement 220V, Single-Phase, 60 Hz
Full-Load Current Rating..... 14.8A
Minimum Circuit Size 20A
Connection Type Cord & Plug
Power Cord Included Yes
Power Cord Length 6-1/2 ft.
Power Cord Gauge 12 AWG
Plug Included No
Recommended Plug Type 6-20
Switch Type ON/OFF Push Button

Motor:

Main

Type..... TEFC Capacitor-Start Induction
Horsepower 3 HP
Voltage 220V
Phase Single-Phase
Amps 14.8A
Speed 3360 RPM
Cycle..... 60 Hz
Power Transfer Direct
Bearings Shielded and Permanently Sealed

Main Specifications:

Operation Information

Sanding Belt Speed.....	5900 FPM
Sanding Belt Length.....	78-3/4"
Sanding Belt Width.....	4"
Number of Profile Rollers.....	7
Profile Roller Sizes.....	3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3"
Grinding Capacity.....	3/4" – 3" O.D.
Grinding Angle Range.....	90° – 30°

Construction

Stand.....	Formed Steel
Body.....	Formed Steel
Rollers.....	Polished Steel
Paint.....	Powder Coated

Other Specifications:

Country of Origin.....	China
Warranty.....	1 Year
Approximate Assembly & Setup Time.....	1 Hour
Serial Number Location.....	ID Label
ISO 9001 Factory.....	Yes
CSA Certified.....	No

Features:

- Convenient ratcheting system for sanding belt tensioning
- Front debris-catching tray
- Rear 3" dust port
- Easy sanding belt alignment
- Top sanding belt access for deburring
- Compound self-aligning vise with side-to-side adjustment to prevent uneven belt wear
- Transparent safety guard
- Removable spark tray

Accessories:

- 7 rollers (3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3")
- Toolbox with service tools