



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0787 4" X 36" HORIZONTAL/VERTICAL BELT SANDER WITH 6" DISC

Product Dimensions:

Weight..... 38 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 17-1/2 x 14-1/2 x 24 in.
Footprint (Length x Width)..... 6 x 15 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 41 lbs.
Length x Width x Height..... 23 x 12 x 13 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 120V, Single-Phase, 60 Hz
Full-Load Current Rating..... 4.3A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 18 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Toggle Safety Switch w/Removable Key

Motors:

Main

Horsepower..... 1/2 HP
Phase..... Single-Phase
Amps..... 4.3A
Speed..... 3600 RPM
Type..... Capacitor-Start Induction
Bearings..... Ball Bearings
Centrifugal Switch/Contacts Type..... N/A

Main Specifications:

Belt Sander Info

Sanding Belt Width..... 4 in.
Sanding Belt Length..... 36 in.
Sanding Belt Speed..... 1900 FPM
Sanding Belt Tilt..... 90 deg.
Max Height of Belt in Vertical Position..... 24-1/2 in.
Belt Tension Release Type..... Quick-Release Lever
Platen Type..... Steel
Platen Length..... 12 in.
Platen Width..... 4-7/8 in.

Disc Sander Info

Disc Diameter..... 6 in.
Disc Speed..... 3600 RPM
Disc Sandpaper Backing Type..... PSA
Table Length..... 6-1/4 in.
Table Width..... 9 in.
Table Tilt..... Left 0, Right 45 deg.
Table-to-Floor Height..... 4-3/4 in.

Construction Materials

Base..... Cast Iron
Table..... Die-Cast Aluminum
Frame..... Cast Iron
Disc..... Aluminum
Miter Gauge..... Plastic and Steel
Paint Type/Finish..... Urethane

Other Related Info

Miter Gauge Slot Width..... 5/8 in.
Miter Gauge Slot Height..... 1/4 in.
Number of Dust Ports..... 1
Dust Port Size..... 2-1/2 in.

Other Specifications:

Country of Origin China
Warranty 1 Year
Approximate Assembly & Setup Time 30 Minutes
Serial Number Location ID Label
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) Yes

Features:

- Built-In dust port
- Fast-tracking adjustment knob
- Quick-release belt lever
- Adjustable miter gauge