



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0803 9" BENCHTOP BANDSAW

Product Dimensions:

Weight..... 42 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 20-3/4 x 17 x 29-1/2 in.
Footprint (Length x Width)..... 15-1/4 x 8-3/8 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 49 lbs.
Length x Width x Height..... 32 x 18 x 14 in.
Must Ship Upright..... No

Electrical:

Power Requirement..... 120V, Single-Phase, 60 Hz
Full-Load Current Rating..... 2.8A
Minimum Circuit Size..... 15A
Power Cord Included..... Yes
Power Cord Length..... 72 in.
Power Cord Gauge..... 18 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Paddle Safety Switch w/Removable Key

Motors:

Main

Horsepower..... 1/3 HP
Phase..... Single-Phase
Amps..... 2.8A
Speed..... 1720 RPM
Type..... ODP Induction
Power Transfer Belt Drive

Main Specifications:

Main Specifications

Bandsaw Size..... 9 in.
Max Cutting Width (Left of Blade)..... 8-7/8 in.
Max Cutting Width (Left of Blade) w/Fence..... 5 in.
Max Cutting Height (Resaw Height)..... 3-5/8 in.
Blade Speeds..... 2460 FPM

Blade Information

Standard Blade Length..... 62 in.
Blade Length Range..... 61-13/16 – 62-3/16 in.
Blade Width Range..... 1/8 – 3/8 in.
Type of Blade Guides..... Ball Bearing
Guide Post Adjustment Type..... Rack & Pinion
Has Quick-Release..... Yes

Table Information

Table Length.....	12 in.
Table Width.....	12 in.
Table Thickness.....	5/8 in.
Table Tilt.....	Left 0, Right 45 deg.
Table Tilt Adjustment Type.....	Rack & Pinion
Floor-to-Table Height.....	13 in.
Fence Locking Position.....	Front
Miter Gauge Included.....	Yes

Construction Materials

Table.....	Cast Aluminum
Trunnion.....	Cast Aluminum
Fence.....	Extruded Aluminum
Base/Stand.....	Pre-Formed Steel
Frame/Body.....	Pre-Formed Steel
Wheels.....	Balanced Aluminum
Tire.....	Rubber
Wheel Cover	Steel
Paint Type/Finish.....	Urethane

Other Related Information

Wheel Diameter.....	9-5/16 in.
Wheel Width.....	3/4 in.
Number of Dust Ports.....	1
Dust Port Size.....	2 in.

Other Specifications:

Country of Origin	China
Warranty	1 Year
Approximate Assembly & Setup Time	30 Minutes
Serial Number Location	ID Label
ISO 9001 Factory	Yes

Features:

Wheels Adjustable for Alignment/Coplanarity
Rack & Pinion Table Tilt
Ball-Bearing Blade Guides
Quick-Release Blade Tension Lever
Extruded Aluminum Rip Fence with Camlock Handle
2" Dust Port
Lower Wheel Brush to Prevent Build-Up of Dust/Pitch on Wheel
Work Light
Made in an ISO 9001 Factory

Accessories Included:

Push Stick
Miter Gauge