



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0803Z 9" BENCHTOP BANDSAW WITH LASER GUIDE

Product Dimensions:

Weight..... 42 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 20-3/4 x 17 x 29-1/2 in.
Footprint (Length x Width)..... 15-1/2 x 6-1/2 in.

Shipping Dimensions:

Type..... Cardboard Box
Content..... Machine
Weight..... 49 lbs.
Length x Width x Height..... 32 x 18 x 14 in.
Must Ship Upright..... No

Electrical:

Power Requirement..... 120V, Single-Phase, 60 Hz
Full-Load Current Rating..... 2.8A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 18 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Paddle Safety Switch w/Removable Key

Motors:

Main

Horsepower..... 1/3 HP
Phase..... Single-Phase
Amps..... 2.8A
Speed..... 1720 RPM
Type..... ODP Induction
Power Transfer Belt

Main Specifications:

Main Specifications

Bandsaw Size..... 9 in.
Max Cutting Width (Left of Blade)..... 9 in.
Max Cutting Width (Left of Blade) w/Fence..... 4-1/2 in.
Max Cutting Height (Resaw Height)..... 3-5/8 in.
Blade Speeds..... 2460 FPM

Blade Information

Standard Blade Length..... 62 in.
Blade Length Range..... 61-13/16 - 62-3/16 in.
Blade Width Range..... 1/8 - 3/8 in.
Type of Blade Guides..... Ball Bearing
Guide Post Adjustment Type..... Rack & Pinion
Has Quick-Release..... Yes

Table Information

Table Length..... 12 in.
Table Width..... 12 in.
Table Thickness..... 5/8 in.
Table Tilt..... 0 - 45 deg.
Table Tilt Adjustment Type..... Rack & Pinion
Floor-to-Table Height..... 13 in.
Fence Locking Position..... Front
Fence is Adjustable for Blade Lead..... Yes
Miter Gauge Included..... Yes

Construction Materials

Table..... Cast Aluminum
Trunnion..... Cast Aluminum
Fence..... Extruded Aluminum
Base/Stand..... Pre-Formed Steel
Frame/Body..... Pre-Formed Steel
Wheels..... Balanced Aluminum
Tire..... Rubber
Wheel Cover Steel
Paint Type/Finish..... Urethane

Other Related Information

Wheel Diameter..... 9-5/16 in.
Wheel Width..... 3/4 in.
Number of Dust Ports..... 1
Dust Port Size..... 2 in.

Other Specifications:

Country of Origin China
Warranty 1 Year
Approximate Assembly & Setup Time 30 Minutes
Serial Number Location ID Label
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

- Laser Sight
- Adjustable Wheels for Alignment/Coplanarity
- Fence Adjustable for Blade Lead
- Rack & Pinion Table Tilt
- Ball-Bearing Blade Guides
- Quick-Release Blade Tension Lever
- Extruded Aluminum Rip Fence with Camlock Handle
- Lower Wheel Brush to Prevent Build-Up of Dust/Pitch on Wheel
- 2" Dust Port
- Chip Blower
- Work Light

Accessories Included:

Push Stick
Miter Gauge