



MACHINE DATA SHEET

© Grizzly Industrial, Inc. • Customer Service: (800) 523-4777 • Tech Support: (570) 546-9663

MODEL G0805 SUPER HEAVY-DUTY ANGLE NOTCHER, 9-GAUGE

Product Dimensions:

Weight 827 lbs.
Width (side-to-side) x Depth (front-to-back) x Height 40 x 26 x 40 in.
Footprint (Length x Width) 27-1/2 x 20-1/2 in.

Shipping Dimensions:

Type Wood Crate
Weight 904 lbs.
Length x Width x Height 37 x 29 x 44 in.
Must Ship Upright Yes

Electrical:

Required Requirement 220V or 440V, 3-Phase, 60 Hz
Prewired Voltage 220V
Full-Load Current Rating 8.6A at 220V, 4.3A at 440V
Minimum Circuit Size 15A at 220V, 15A at 440V
Connection Type Cord & Plug at 220V, Permanent (Hardwire) at 440V
Power Cord Included Yes
Power Cord Length 6 ft.
Power Cord Gauge 14 AWG
Plug Included No
Recommended Plug Type 15-15 for 220V
Switch Type ON/OFF Push Button Switch

Motor:

Main

Type TEFC Induction
Horsepower 3 HP
Phase 3-Phase
Amps 8.6A/4.3A
Speed 1720 RPM
Power Transfer Direct Drive
Bearings Shielded & Permanently Sealed

Main Specifications:

Operation Information

Maximum Thickness Mild Steel.....	9 Gauge
Maximum Hydraulic Power.....	12 Tons
Maximum Notch Size	7-7/8 x 7-7/8 in.
Notch Angle.....	90 deg.
Strokes Per Minute.....	50
Table Size (Length x Width).....	23-1/2 x 27-1/2 in.
Table Thickness	1-7/8 in.
Floor-to-Table Height	35-1/2 in.
Oil Tank Capacity	5 gal.

Construction

Base	Steel
Table.....	Cast Iron
Headstock/Ram	Cast Iron
Guard.....	Acrylic
Shear Blades	Precision-Ground Hardened Steel
Paint/Finish.....	Enamel

Other Specifications:

Country of Origin.....	Taiwan
Warranty.....	1 Year
Approximate Assembly & Setup Time	30 Minutes
Serial Number Location	ID Label
ISO 9001 Factory.....	No
CSA Certified	No

Features:

- 9-Gauge Mild Steel Cutting Capacity
- Emergency Stop Button on Foot-Control Pedestal
- 12-Ton Force Capacity
- 7⁷/₈" x 7⁷/₈" Max Notch Dimension
- 50 Strokes Per Minute
- Foot-Controlled, Hydraulic-Powered Cutting Operation
- Large 23¹/₂" x 27¹/₂" Cast Iron Table Features Angle Guides and Inch/Metric Scales