



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0817 14" SUPER HD 2 HP RESAW BANDSAW WITH FOOT BRAKE

### Product Dimensions:

Weight..... 319 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 29 x 32-1/2 x 76 in.  
Footprint (Length x Width)..... 24 x 18 in.

### Shipping Dimensions:

Type..... Wood Crate  
Content..... Machine  
Weight..... 388 lbs.  
Length x Width x Height..... 30 x 24 x 79 in.  
Must Ship Upright..... Yes

### Electrical:

Power Requirement..... 110V or 220V, Single-Phase, 60Hz  
Prewired Voltage..... 110V  
Full-Load Current Rating..... 19A at 110V, 9.5A at 220V  
Minimum Circuit Size..... 30A at 110V, 15A at 220V  
Connection Type..... Cord & Plug  
Power Cord Included..... Yes  
Power Cord Length..... 6 ft.  
Power Cord Gauge..... 12 AWG  
Plug Included..... Yes  
Included Plug Type..... 5-20  
Recommended Plug Type..... 6-15 for 220V  
Switch Type..... Control Panel w/Magnetic Switch Protection & Lockout Key

### Motors:

#### Main

Horsepower..... 2 HP  
Phase..... Single-Phase  
Amps..... 19A/9.5A  
Speed..... 1720 RPM  
Type..... TEFC Capacitor-Start Induction  
Power Transfer ..... Belt Drive  
Bearings..... Shielded & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... External

### Main Specifications:

#### Main Specifications

Bandsaw Size..... 14 in.  
Max Cutting Width (Left of Blade)..... 13-1/2 in.  
Max Cutting Width (Left of Blade) w/Fence..... 12 in.  
Max Cutting Height (Resaw Height)..... 14 in.  
Blade Speeds..... 2820 FPM

**Blade Information**

Standard Blade Length.....	120 in.
Blade Width Range.....	1/8–3/4 in.
Type of Blade Guides.....	Dual Roller Bearings
Guide Post Adjustment Type.....	Knob
Has Quick-Release.....	Yes

**Table Information**

Table Length.....	21-3/4 in.
Table Width.....	16-1/8 in.
Table Thickness.....	1-1/2 in.
Table Tilt.....	Left 5, Right 45 Deg.
Table Tilt Adjustment Type.....	Lever
Floor-to-Table Height.....	37 in.
Fence Locking Position.....	Front
Fence is Adjustable for Blade Lead.....	Yes
Resaw Fence Attachment Included.....	Yes
Miter Gauge Included.....	Yes

**Construction Materials**

Table.....	Cast Iron
Trunnion.....	Cast Iron
Fence.....	Extruded Aluminum
Base/Stand.....	Sheet Metal
Frame/Body.....	Sheet Metal
Wheels.....	Cast Iron
Tire.....	Polyurethane
Wheel Cover .....	Sheet Metal
Paint Type/Finish.....	Powder Coat

**Other Related Information**

Wheel Diameter.....	14 in.
Wheel Width.....	1-1/8 in.
Number of Dust Ports.....	2
Dust Port Size.....	4 in.
Compatible Mobile Base.....	D2057A

**Other Specifications:**

Country of Origin .....	Taiwan
Warranty .....	1 Year
Approximate Assembly & Setup Time .....	1 Hour
Serial Number Location .....	Machine ID Label
ISO 9001 Factory .....	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) .....	Yes

**Features:**

- 14" Resaw Capacity
- 2 HP, 110V/220V (Prewired 110V), Single-Phase
- Ball-Bearing Blade Guides
- Foot-Operated Brake System
- Modular Blade-Guide Design for Easy Changeovers Between Styles
- Lever-Action Table Trunnion for Quick Table Tilt Adjustment
- Cast-Iron Fence with 2-Position Extruded Aluminum Resaw Fence
- Storage Area for Extra Blades and Miter Gauge When Not In Use
- Cast-Iron Wheels and Table Trunnion
- Included Miter Gauge
- Blade Tension Indicator