



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0826 EASY FEEDER POWER FEEDER

### Product Dimensions:

Weight..... 117 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 37-1/2 x 20-1/2 x 29-1/2 in.  
Footprint (Length x Width)..... 5-1/2 x 6 in.

### Shipping Dimensions:

#### Carton #1

Type..... Cardboard Box  
Content..... Machine  
Weight..... 54 lbs.  
Length x Width x Height..... 23 x 13 x 12 in.  
Must Ship Upright..... No

#### Carton #2

Type..... Cardboard Box  
Content..... Stand  
Weight..... 71 lbs.  
Length x Width x Height..... 31 x 13 x 13 in.  
Must Ship Upright..... No

### Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz  
Full-Load Current Rating..... 2.3A  
Minimum Circuit Size..... 15A  
Connection Type..... Cord & Plug  
Power Cord Included..... Yes  
Power Cord Length..... 9 ft.  
Power Cord Gauge..... 18 AWG  
Plug Included..... Yes  
Included Plug Type..... 6-15  
Switch Type..... Push-Button ON/OFF

### Motors:

#### Main

Horsepower..... 500 Watt (2/3 HP)  
Phase..... Single-Phase  
Amps..... 2.3A  
Speed..... 350 – 4800 RPM  
Type..... BLDC  
Power Transfer ..... Gear Drive  
Bearings..... Sealed & Permanently Lubricated  
Centrifugal Switch/Contacts Type..... N/A

### Main Specifications:

#### Workpiece Capacities

Minimum Workpiece Length..... 6 in.

**Operation Info**

Number of Feed Speeds..... Variable  
Feed Speeds..... 7 – 72 FPM  
Swing..... 360 deg.  
Vertical Movement..... 6-11/16 in.  
Horizontal Movement..... 17 in.  
Rotation..... Forward/Reverse

**Roller Info**

Number of Rollers..... 3  
Roller Width..... 2-5/16 in.  
Roller Diameter..... 4-3/4 in.  
Roller Suspension..... 3/4 in.  
Maximum Height Rollers Parallel Table Surface..... 7-1/2 in.

**Construction Info**

Roller..... Rubber  
Housing..... Cast Aluminum  
Supports..... Cast Iron  
Column..... Cast Iron  
Paint Type/Finish..... Enamel

**Other**

Column Diameter..... 2-1/4 in.

**Other Specifications:**

Country of Origin ..... Taiwan  
Warranty ..... 1 Year  
Approximate Assembly & Setup Time ..... 45 Minutes  
Serial Number Location ..... ID Label  
ISO 9001 Factory ..... Yes

**Features:**

- Variable-Speed Feed Adjustment Dial
- Large Feed Speed Digital Readout
- Push-Button ON/OFF Switch and Feed Direction
- Crank Handle Vertical Adjustment
- 7" Max. Workpiece Clearance
- Rack-and-Pinion Horizontal Movement