



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0879 FLUX CORE MIG WELDER

Product Dimensions:

Weight 33 lbs.
Width (side-to-side) x Depth (front-to-back) x Height 8-1/2 x 15 x 14 in.

Shipping Dimensions:

Type Cardboard
Content Machine
Weight 38 lbs.
Length x Width x Height 20 x 12 x 15 in.
Must Ship Upright Yes

Electrical:

Power Requirement 120V, Single-Phase, 60 Hz
Minimum Circuit Size 20A
Output Current / Duty Cycle (LOW) 20% @ 60A
Output Current / Duty Cycle (HIGH) 10% @ 70A
Power Cord Length 7 ft.
Power Cord Gauge 14 AWG
Included Plug Type 5-15
Switch Type ON/OFF Rocker

Operation Information:

Maximum Material Thickness 3/16 in.
Wire Feed Speed Range (Inches per Minute) 200 - 600 IPM
Wire Diameter Range 0.030 - 0.035 in.
Maximum Wire Spool Diameter 3-7/8 in.
Torch Cable Length 7 ft.
Ground Cable Length 6-1/2 ft.

Other Specifications:

Country of Origin China
Warranty 1 Year
Approximate Assembly & Setup Time 15 Minutes
Serial Number Location Machine ID Label
Housing Protection Class IP21
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) Yes

Features:

- Adjustable Wire Speed Control
- Low 50A and High 80A Modes
- Capable of Welding Steel and Stainless Steel

Accessories:

- Brush/Chipping Hammer
- 0.030 in. & 0.035 in. Tips
- 1 lb. of 0.035 in. Flux Wire