



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0885 5" PORTABLE METAL-CUTTING BANDSAW

### Product Dimensions:

Weight..... 44 lbs.  
Width (side-to-side) x Depth (front-to-back) x Height..... 27 x 25 x 26 in.  
Footprint (Length x Width)..... 12-1/2 x 16 in.

### Shipping Dimensions:

Type..... Cardboard Box  
Content..... Machine  
Weight..... 51 lbs.  
Length x Width x Height..... 29 x 15 x 18 in.  
Must Ship Upright..... Yes

### Electrical:

Power Requirement..... 120V, Single-Phase, 60 Hz  
Full-Load Current Rating..... 5A  
Minimum Circuit Size..... 15A  
Connection Type..... Cord & Plug  
Power Cord Included..... Yes  
Power Cord Length..... 6 ft.  
Power Cord Gauge..... 18 AWG  
Included Plug Type..... 5-15  
Switch Type..... On/Off Push Button

### Motors:

#### Main

Horsepower..... 1/2 HP  
Phase..... Single-Phase  
Amps..... 5A  
Speed..... 2000 - 4200 RPM  
Type..... Universal  
Power Transfer ..... Direct  
Bearings..... Shielded & Permanently Lubricated

### Main Specifications:

#### Operation Info

Blade Speeds..... 100 - 260 FPM  
Std. Blade Length..... 56-1/2 in.  
Blade Length Range..... 1/2 in.

#### Cutting Capacities

Angle Cuts..... 0 - 60 deg.  
Vise Jaw Depth..... 5 in.  
Vise Jaw Height..... 2-3/4 in.  
Max. Capacity Rectangular Height at 90 Deg..... 4-3/4 in.  
Max. Capacity Rectangular Width at 90 Deg..... 5 in.  
Max. Capacity Round at 90 Deg..... 4-3/4 in.

**Construction**

Table..... Cast Iron  
 Upper Wheel..... Cast Iron  
 Lower Wheel..... Cast Iron  
 Body..... Aluminum  
 Base..... Steel  
 Wheel Cover..... Steel  
 Paint Type/Finish..... Powder Coated

**Other**

Blade Guides..... Ball Bearing

**Other Specifications:**

Country of Origin ..... Taiwan  
 Warranty ..... 1 Year  
 Approximate Assembly & Setup Time ..... 15 Minutes  
 Serial Number Location ..... Machine ID Label  
 ISO 9001 Factory ..... No  
 Certified by a Nationally Recognized Testing Laboratory (NRTL) ..... No

**Features:**

- Variable-Speed Control
- Built-In Vise
- Handle with ON/OFF Trigger
- 0-60 Degree Angle Cuts