



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0897 4" X 48" 2-WHEEL METAL BELT GRINDER/SANDER

Product Dimensions:

Weight..... 75 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 15 x 25-1/2 x 35-1/2 in.
Footprint (Length x Width)..... 16-1/2 x 12 in.

Shipping Dimensions:

Type..... Wood Crate
Content..... Machine
Weight..... 86 lbs.
Length x Width x Height..... 25 x 17 x 17 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz
Full-Load Current Rating..... 13.8A
Minimum Circuit Size..... 20A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 14 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... ON/OFF Push Button w/Safety Cover

Motors:

Main

Horsepower..... 2 HP
Phase..... Single-Phase
Amps..... 13.8A
Speed..... 3400 RPM
Type..... TEFC Capacitor-Run Induction
Power Transfer Direct Drive
Bearings..... Shielded & Permanently Lubricated

Main Specifications:

Belt Sander Info

Sanding Belt Width..... 4 in.
Sanding Belt Length..... 48 in.
Sanding Belt Speed..... 4500 FPM
Contact Wheel Diameter..... 5 in.
Contact Wheel Width..... 4 in.
Belt Tension Release Type..... Quick Release
Platen Type..... Graphite Coated
Platen Length..... 11-1/8 in.
Platen Width..... 4-3/4 in.

Construction Materials

Stand..... Formed Steel
Frame..... Formed Steel
Paint Type/Finish..... Enamel

Other Related Info

Number of Dust Ports..... 1
Dust Port Size..... 3 in.

Other Specifications:

Country of Origin China
Warranty 1 Year
Approximate Assembly & Setup Time 1 Hour
Serial Number Location ID Label
ISO 9001 Factory No

Features:

- Work Stop for Use with Platen
- Work Rest for Use with Contact Wheel
- Removable Spark Trap
- 3" Dust Port
- Transparent Safety Guard
- Single-Knob Tracking Adjustment
- Spring-Loaded Quick Release Belt