



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0928 60-GALLON 5 HP EXTREME-SERIES AIR COMPRESSOR

Product Dimensions:

Weight 364 lbs.
Width (side-to-side) x Depth (front-to-back) x Height 29-1/2 x 23 x 74 in.
Footprint (Length x Width) 21 x 20 in.

Shipping Dimensions:

Type Cardboard Box
Content Machine
Weight 424 lbs.
Length x Width x Height 40 x 31 x 80 in.
Must Ship Upright Yes

Electrical:

Power Requirement 230V, Single-Phase, 60 Hz
Full-Load Current Rating 22A
Minimum Circuit Size 30A
Connection Type Permanent (Hardwire to Shutoff Switch)
Switch Type Pressure Switch w/Motor Reset Button

Motors:

Main

Horsepower 5 HP
Phase Single-Phase
Amps 22A
Speed 3450 RPM
Type ODP Capacitor-Start Induction
Power Transfer Belt
Bearings Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type Internal

Main Specifications:

Operation Information

Compressor Style Vertical
Pump Type Two-Stage
Max. Airflow/Delivery (at 100 PSI) 15.3 CFM
Max. Airflow/Delivery (at 175 PSI) 13.5 CFM
Cut-Out Pressure 175 PSI
Cut-In Pressure 145 PSI
Duty Cycle 75/25
Tank Size 60 Gallons
Number of Cylinders 2
Pump Lubrication Grizzly Model T28041 or 100% Full Synthetic Non-Detergent Air Compressor Oil
Drain Valve Type Ball Valve
Regulator No

Output Port Information

Connection Type Female-Threaded Fitting
Connection Size 3/4" NPT
Number of Connections 1
Hose Included No

Construction Information

Tank.....Steel
Valves..... Brass/Brass-Coated Steel
Paint Type/Finish..... Powder Coated

Other Specifications:

Country of Origin..... USA
Warranty..... 2 Years
Approximate Assembly & Setup Time 2-3 Hours
Serial Number Location Factory Specification Tag
Sound Rating 80 dB

Features:

- 60-Gallon Tank with Maximum Airflow of 13.5 CFM at 175 PSI
- Ball-Valve Drain Control
- Fan Pulley and Cooling Fin Design to Keep Compressor Cool
- Oil Sight Glass
- Low Pump RPM for Extended Life