



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0955 60-GALLON 5 HP EXTREME-SERIES AIR COMPRESSOR

Product Dimensions:

Weight 325 lbs.
Width (side-to-side) x Depth (front-to-back) x Height 30 x 22 x 68 in.
Footprint (Length x Width) 22-1/2 x 19-1/2 in.

Shipping Dimensions:

Type Wood Crate
Content Machine
Weight 345 lbs.
Length x Width x Height 31 x 24 x 74 in.
Must Ship Upright Yes

Electrical:

Power Requirement 230V, Single-Phase, 60 Hz
Full-Load Current Rating 22.5A
Minimum Circuit Size 30A
Connection Type Permanent (Hardwire to Shutoff Switch)
Switch Type Pressure Switch w/Motor Reset Button

Motors:

Main

Horsepower 5 HP
Phase Single-Phase
Amps 22.5A
Speed 3450 RPM
Type ODP Capacitor-Start Induction
Power Transfer Belt
Bearings Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type External

Main Specifications:

Operation Information

Compressor Style Vertical
Pump Type One-Stage
Max. Airflow/Delivery (at 40 PSI) 20 SCFM
Max. Airflow/Delivery (at 90 PSI) 18 SCFM
Max. Pressure 150 PSI
Cut-Out Pressure 125 PSI
Cut-In Pressure 95 PSI
Duty Cycle 65/35
Tank Size 60 Gallons
Number of Cylinders 3
Pump Lubrication Grizzly Model T28041 or 100% Fully Synthetic Non-Detergent Air Compressor Oil
Drain Valve Type Ball Valve
Regulator No

Output Port Information

Connection Type Female Threaded Ball Valve
Connection Size 1/2" NPT
Number of Connections 1
Hose Included No

Construction Information

Tank Steel
Valves Brass
Paint Type/Finish Enamel

Other Specifications:

Country of Origin USA
Warranty 1 Year
Approximate Assembly & Setup Time 30 Minutes
Serial Number Location ID Label
Sound Rating 79 - 81 dB

Features:

60-Gallon Tank with Maximum Airflow of 18 CFM at 90 PSI
Ball-Valve Drain Control
Fan Pulley and Cooling Fin Design to Keep Compressor Cool
Oil Sight Glass
W-Cylinder Cast-Iron Air Compressor Pump