



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0962 10" 2 HP OPEN-STAND HYBRID TABLE SAW

Product Dimensions:

Weight..... 243 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 64 x 40-1/2 x 36 in.
Footprint (Length x Width)..... 21 x 19-1/2 in.
Space Required for Full Range of Movement (Width x Depth)..... 64 x 37-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard Box
Content..... Machine
Weight..... 259 lbs.
Length x Width x Height..... 40 x 30 x 29 in.

Carton #2

Type..... Cardboard Box
Content..... Fence, Rails, and Hardware
Weight..... 38 lbs.
Length x Width x Height..... 66 x 16 x 6 in.

Electrical:

Power Requirement..... 120V or 240V, Single-Phase, 60 Hz
Prewired Voltage..... 120V
Full-Load Current Rating..... 15A at 120V, 7.5A at 240V
Minimum Circuit Size..... 20A at 120V, 15A at 240V
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 72 in.
Power Cord Gauge..... 14 AWG
Plug Included..... Yes
Included Plug Type..... NEMA 5-15 for 120V
Recommended Plug Type..... NEMA 6-15 for 240V
Switch Type..... START/STOP Push Button w/Lockout Pin

Motors:

Main

Horsepower..... 2 HP
Phase..... Single-Phase
Amps..... 15A at 120V, 7.5A at 240V
Speed..... 3450 RPM
Type..... Capacitor-Start Induction
Power Transfer Belt
Bearings..... Shielded & Permanently Lubricated

Main Specifications:

Main Information

Table Saw Type.....	Hybrid
Maximum Standard Blade Diameter.....	10 in.
Arbor Size.....	5/8 in.
Arbor Speed.....	3450 RPM
Maximum Width of Dado.....	13/16 in.
Blade Tilt Direction.....	Left
Max Blade Tilt.....	45 deg.
Maximum Depth of Cut At 90 Degrees.....	3-1/4 in.
Maximum Depth of Cut At 45 Degrees.....	2-1/4 in.
Max Rip Right of Blade w/Included Fence & Rails.....	30 in.
Max Rip Left of Blade w/Included Fence & Rails.....	15 in.

Additional Blade Information

Included Blade Information.....	10" x 40T
Riving Knife/Spreader Thickness.....	0.090 in.
Required Blade Body Thickness.....	0.060 - 0.086 in.
Required Blade Kerf Thickness.....	0.094 - 0.126 in.
Rim Speed at Max Blade Diameter.....	9,025 FPM

Table Information

Floor to Table Height.....	35-3/4 in.
Table Size with Extension Wings Width.....	40-1/4 in.
Table Size with Extension Wings Depth.....	27 in.
Distance Front of Table to Center of Blade.....	15-1/2 in.
Distance Front of Table to Blade At Maximum Cut.....	11-1/2 in.
Main Table Size Thickness.....	1-5/8 in.

Fence Information

Fence Type.....	Camlock T-Shape w/Aluminum Face
Fence Size Length.....	35-3/4 in.
Fence Size Width.....	3-1/8 in.
Fence Size Height.....	2-7/16 in.
Fence Rail Type.....	Extruded Aluminum
Fence Rail Length.....	64 in.
Fence Rail Width.....	3-1/8 in.
Fence Rail Height.....	2-1/4 in.

Miter Gauge Information

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Miter Gauge Slot Size Height.....	3/8 in.

Construction

Table.....	Cast Iron
Wings.....	Stamped Steel
Cabinet.....	Pre-Formed Steel
Trunnions.....	Cast Iron
Fence Assembly.....	Aluminum
Rails.....	Aluminum
Miter Gauge Construction.....	Aluminum
Guard.....	Aluminum & Plastic
Body/Cabinet Paint Type/Finish.....	Powder Coated
Arbor Bearings.....	Shielded & Permanently Lubricated

Other Related Information

Number of Dust Ports.....	1
Dust Port Size.....	4 in.
Compatible Mobile Base.....	T28000

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 1 Hour
Serial Number Location ID Label
Sound Rating 81 - 83 dB
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) Yes

Features:

Precision-Ground Cast-Iron Table
Powder Coated Steel Extension Wings
Cast Iron Trunnions
Easy-Glide Fence System
Quick-Release Blade Guard Assembly
4" Dust Port
T-Slot Miter Gauge
Built-In Mobile Base

Accessories Included:

10" x 40T Ripping Blade
Safety Push Stick
Standard Table Insert
Dado Table Insert
Miter Gauge
Hex Wrenches 2.5, 3, 4, 5, 6, 8mm
Two Arbor Wrenches
20A Circuit Breaker for 240V Conversion