



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0969 21" VS SCROLL SAW WITH FOOT PEDAL

Product Dimensions:

Weight 79 lbs.
Width (side-to-side) x Depth (front-to-back) x Height 20-1/2 x 37 x 17-1/2 in.
Footprint (Length x Width) 17 x 15 in.

Shipping Dimensions:

Type Cardboard Box
Content Machine
Weight 100 lbs.
Length x Width x Height 41 x 24 x 20 in.
Must Ship Upright Yes

Electrical:

Power Requirement 110V, Single-Phase, 60 Hz
Full-Load Current Rating 1.3A
Minimum Circuit Size 15A
Connection Type Cord & Plug
Power Cord Included Yes
Power Cord Length 72 in.
Power Cord Gauge 18 AWG
Plug Included Yes
Included Plug Type 5-15
Switch Type Rocker ON/OFF w/Variable-Speed Dial

Motor:

Main

Horsepower 50W
Phase Single-Phase
Amps 1.3A
Speed 1550 RPM
Type Universal (DC)
Power Transfer Direct
Bearings Sealed & Permanently Lubricated

Main Specifications:

Capacities

Depth of Throat 21 in.
Maximum Cutting Height 1-3/4 in.
Maximum Cutting Height at 22-1/2 Degrees 1-1/2 in.
Maximum Cutting Height at 30 Degrees 1-5/16 in.
Maximum Cutting Height at 45 Degrees 7/8 in.
Maximum Cutting Depth 21 in.

Blade & Movement

Blade Type	Plain-End
Blade Length	5 in.
Blade Width Range	3/32 in.
Blade Stroke	3/4 in.
Blade Strokes Per Minute (SPM)	400 - 1550 SPM
Blade & Arm Tilt	0 - 45 deg. L/R (w/Dust Port Removed)
Blade & Arm Tilt Adjustment Type	Manual

Table Information

Table Length	28-7/16 in.
Table Width	20-1/8 in.
Table Thickness	1/4 in.

Construction

Table	Steel
Body	Steel
Blade Guard	Stainless Steel
Paint Type/Finish	Enamel

Other Information

Number of Dust Ports	1
Dust Port Size	2-1/2 in.

Other Specifications:

Country of Origin	Taiwan
Warranty	1 Year
Approximate Assembly & Setup Time	30 Minutes
Serial Number Location	ID Label
ISO 9001 Factory	Yes

Features:

Foot Pedal Switch
Tool-Less Blade Holder Accepts Plain-End Blades
Variable Blade Speed
Arm Assembly Raises for Easy Blade Access
Stationary Steel Table 20-1/8" x 28-7/16"
Blade & Arm Tilt 45° Side to Side (w/Dust Port Removed)
Positive Indexing Pin Holes at 0°, 45°, 30° and 22-1/2° in Both Directions
Flexible Sawdust Blower
Hold-Down Shoe
Dust Port 2-1/2"

Accessories:

Plain-End Blade 5"
Hex Wrench 3mm
Optional Stand Available (T33905)