



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0971 51" POWERED SLIP ROLL

Product Dimensions:

Weight..... 805 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 86-1/2 x 37 x 48 in.
Footprint (Length x Width)..... 58-1/2 x 20-1/2 in.

Shipping Dimensions:

Type..... Wood Crate
Content..... Machine
Weight..... 920 lbs.
Length x Width x Height..... 74 x 27 x 51 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz
Full-Load Current Rating..... 14A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 60 in.
Power Cord Gauge..... 14 AWG
Plug Included..... Yes
Included Plug Type..... NEMA 5-15
Switch Type..... ON/OFF Push Button w/Foot Pedal Controls

Motors:

Main

Horsepower..... 1 HP
Phase..... Single-Phase
Amps..... 14A
Speed..... 1650 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Chain
Bearings..... Sealed & Permanently Lubricated

Main Specifications:

Capacities

Maximum Width..... 51 in.
Maximum Thickness Mild Steel..... 16 Gauge
Slip Roll Minimum Cylinder Diameter..... 3 in.
Slip Roll Roller Diameter..... 3 in.
Slip Roll Wire Sizes..... 5/16, 3/8, 1/2 in.

Construction

Frame..... Steel
Head and Tail Supports..... Steel
Rollers..... Hardened Steel

Other Specifications:

Country of Origin	China
Warranty	1 Year
Approximate Assembly & Setup Time	30 Minutes
Serial Number Location	ID Label
ISO 9001 Factory	Yes

Features:

- 1 HP Motor Powers Two Rollers
- 51" Maximum Capacity
- 360 Degree Dual-Direction Actuated Cable Safety Switch
- Forward/Reverse Foot Pedal Controls w/Emergency Stop Button
- Hardened Steel Gearing and Rollers
- Handwheel Adjustable Rollers
- Quick-Release Top Roller
- Three Roller Grooves for Rolling Wire or Rods (5/16", 3/8", and 1/2")
- Hammertone Urethane Paint Finish