



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

GRIZZLY MODEL G1022SM 10" TABLE SAW

Design TypeFloor Model

Overall Dimensions:

Table Height37"
Table Size27 $\frac{1}{8}$ " D x 20 $\frac{1}{8}$ " W
Size With Extension Wings27 $\frac{1}{8}$ " D x 40 $\frac{5}{8}$ " W
With Wings and Fence Rails48" W x 44" D
Miter Gauge T-Slot $\frac{3}{8}$ " x $\frac{3}{4}$ "
Weight (Net)240 lbs.
Weight (Shipping)250 lbs.
Box # 1 Size37 $\frac{1}{2}$ " L x 23" W x 18 $\frac{1}{2}$ " H
Box # 2 Size46" L x 3" W x 1 $\frac{1}{2}$ " H
Footprint21" x 25"

Construction:

TableGround Cast Iron
StandPre-formed Steel
Miter GaugeAluminum / Steel
TrunnionsCast Iron
BearingsShielded and Lubricated Ball Bearings
FenceSingle Lever, Front & Rear Locking w/ Micro Adjust Knob
Rails44" x 1 $\frac{3}{8}$ " Chrome Plated Tubing
GuardSteel and Clear Plastic
WingsFormed Sheet Steel

Cutting Capacity:

Maximum Blade Diameter10"
Maximum Depth of Cut at 90°3 $\frac{1}{8}$ "
Blade Tilt0°-45° Right
Maximum Depth of Cut at 45°2 $\frac{1}{8}$ "
Maximum Rip to Right of Blade (Standard)24"
Maximum Rip to Right of Blade (Optional Extension Rails)48"
Maximum Rip to Left of Blade11"
Distance from Front of Table to Center of Blade17"
Distance from Front of Table to Front of Blade12"
Maximum Width of Dado Cut1 $\frac{3}{16}$ "

Motor:

TypeTEFC Capacitor Start Induction
Horsepower1 $\frac{1}{2}$ HP
Phase / CycleSingle Phase / 60 HZ
Voltage110 / 220V
Prewired110V
Amps16 / 8A
Hertz and RPM60Hz / 3450 RPM
Power TransferBelt Drive
SwitchON/OFF Push Button

Arbor:

Dimensions $\frac{5}{8}$ " x 1 $\frac{1}{4}$ "
Speed4,700 RPM

Features:

.....Includes Table Inserts for Standard Blade and Dado Blade

Specifications, while deemed accurate, are not guaranteed.