



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

GRIZZLY MODEL G1022Z TABLE SAW

Design TypeFloor Model

Overall Dimensions:

Table Height37"
Table Size27 $\frac{1}{8}$ " D x 20 $\frac{1}{8}$ " W
Table Size With Extension Wings27 $\frac{1}{8}$ " D x 40 $\frac{5}{8}$ " W
Table With Wings and Fence Rails48" W x 44" D
Miter Gauge T-Slot $\frac{3}{8}$ " x $\frac{3}{4}$ "
Weight (Net)240 lbs.
Weight (Shipping).....250 lbs.
Box # 1 Size36" L x 18 $\frac{1}{2}$ " W x 25" H
Box # 2 Size46" L x 3" W x 2" H
Box # 3 Size12" L x 12" W x 5" H
Footprint21" x 25"

Construction:

TableGround Cast Iron
StandPre-formed Steel
Miter GaugeAluminum / Steel
TrunnionsCast Iron
Bearings.....Shielded and Lubricated Ball Bearings
FenceSingle Lever; Front & Rear Locking w/ Micro Adjust Knob;
.....Heavy Extruded Aluminum with Tee Slot Top
Rails44" x 1 $\frac{3}{8}$ " Chrome Plated Tubing
GuardSteel and Clear Plastic
Wings.....Ground Cast Iron, Open Ribbed Design

Cutting Capacity:

Maximum Blade Diameter10"
Maximum Depth of Cut at 90°3 $\frac{1}{8}$ "
Blade Tilt0°-45° Right
Maximum Depth of Cut at 45°2 $\frac{1}{8}$ "
Maximum Rip to Right of Blade (Standard).....24"
Maximum Rip to Right of Blade (Optional Extension Rails)48"
Maximum Rip to Left of Blade11"
Distance from Front of Table to Center of Blade17"
Distance from Front of Table to Front of Blade.....12"
Maximum Width of Dado Cut $\frac{13}{16}$ "

Motor:

TypeTEFC Capacitor Start Induction
Horsepower1 $\frac{1}{2}$ HP
Phase / CycleSingle Phase / 60 HZ
Voltage.....110 / 220V
Prewired110V
Amps16 / 8A
Hertz and RPM.....60Hz / 3450 RPM
Power TransferBelt Drive
SwitchON/OFF Push Button

Arbor:

Dimension..... $\frac{5}{8}$ " x 1 $\frac{1}{4}$ "
Speed4,700 RPM

Features:

.....Includes Table Inserts for Standard Blade and Dado Blade
Specifications, while deemed accurate, are not guaranteed.