



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

GRIZZLY MODELS G1022ZF, ZFX, PROZ, & PROZX

Design TypeFloor Model

Overall Dimensions:

Table Height37"
Table Size27 $\frac{1}{8}$ " D x 20 $\frac{1}{8}$ " W
Table Size With Extension Wings27 $\frac{1}{8}$ " D x 40 $\frac{5}{8}$ " W
Overall Dimensions – With Wings and Fence Rails50" D x 52 $\frac{1}{2}$ " W
Miter Gauge T-Slot $\frac{3}{8}$ " x $\frac{3}{4}$ "
Blade Tilt0°-45° Right
Weight (Net)325 lbs.
Weight (Shipping)340 lbs.
Box # 1 Size (Base)37 $\frac{1}{2}$ " L x 22" W x 22 $\frac{1}{2}$ " H
Box # 2 Size (Fence)49" L x 15 $\frac{1}{2}$ " W x 9" H
Box # 3 Size (Accessories)14" L x 14" W x 6" H
Box # 4 Size (Motor)10 $\frac{1}{4}$ " L x 16" W x 9 $\frac{3}{4}$ " H
Footprint21" x 25"

Construction:

TableGround Cast Iron
StandPre-formed Steel
Miter GaugeCast Iron / Steel; Adjusts for Side Play
TrunnionsCast Iron
BearingsShielded and Lubricated Ball Bearings
FenceSHOP FOX® Heavy-Duty (PROZ: SHOP FOX® Classic
GuardSteel and Clear Plastic
WingsPrecision-Ground Cast Iron

Cutting Capacity:

Maximum Blade Diameter10"
Maximum Depth of Cut at 90°3 $\frac{1}{8}$ "
Maximum Depth of Cut at 45°2 $\frac{1}{8}$ "
Maximum Rip to Right of Blade (Standard)25"
Maximum Rip to Right of Blade (Optional Extension Rails)48"
Maximum Rip to Left of Blade11"
Distance from Front of Table to Center of Blade17 $\frac{1}{4}$ "
Distance from Front of Table to Front of Blade12 $\frac{1}{2}$ "
Maximum Width of Dado Cut1 $\frac{3}{16}$ "

Motor:	ZF	ZFX	PROZ	PROZX
Type.....		TEFC Capacitor Start Induction.....		
Horsepower.....	1 $\frac{1}{2}$ HP.....	2 HP.....	2 HP.....	2 HP.....
Phase / Cycle.....		Single Phase / 60 HZ.....		
Voltage.....		110 / 220V.....		
Prewired.....	110V.....	220V.....	220V.....	220V.....
Amps.....	17 / 8.5A.....	26 / 13A.....	26 / 13A.....	26 / 13A.....
RPM.....		3450 RPM.....		
Power Transfer.....		Power Twist® Link Belt Drive.....		
Switch.....		ON/OFF Push Button.....		

Arbor:

Dimension $\frac{5}{8}$ " x 1 $\frac{1}{4}$ "
Speed4,700 RPM

Features:

.....Includes Table Inserts for Standard Blade and Dado Blade
.....U.S.A. Motor, 4" Ported Dust Hood, Link Belt, Rail Mounted Switch

Specifications, while deemed accurate, are not guaranteed.