



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1023S110 10" TABLE SAW 2 HP SINGLE-PHASE 110V

Product Dimensions:

Weight..... 340 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 50 x 31-5/16 x 34 in.
Footprint (Length x Width)..... 20 x 20 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard Box
Content..... Machine
Weight..... 427 lbs.
Length x Width x Height..... 0 x 0 x 0 in.

Carton #2

Type..... Cardboard Box
Content..... Fence
Weight..... 77 lbs.
Length x Width x Height..... 57 x 20 x 7 in.

Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz
Prewired Voltage..... 110V
Full-Load Current Rating..... 24A
Minimum Circuit Size..... 30A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 10 ft.
Power Cord Gauge..... 10 AWG
Plug Included..... No
Switch Type..... Magnetic Switch w/Thermal Overload Protection

Motors:

Main

Horsepower..... 2 HP
Phase..... Single-Phase
Amps..... 24A
Speed..... 3450 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Triple V-Belt Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Main Information

Table Saw Type.....	Cabinet
Maximum Standard Blade Diameter.....	10 in.
Arbor Size.....	5/8 in.
Arbor Speed.....	4200 RPM
Maximum Width of Dado.....	13/16 in.
Blade Tilt Direction.....	Right
Max Blade Tilt.....	45 deg.
Maximum Depth of Cut At 90 Degrees.....	3-1/8 in.
Maximum Depth of Cut At 45 Degrees.....	2-1/8 in.
Max Rip Right of Blade w/Included Fence & Rails.....	26 in.
Max Rip Left of Blade w/Included Fence & Rails.....	8 in.

Additional Blade Information

Rim Speed at Max Blade Diameter.....	11,000 FPM
--------------------------------------	------------

Table Information

Floor to Table Height.....	34 in.
Table Size with Extension Wings Width.....	40 in.
Table Size with Extension Wings Depth.....	27 in.
Distance Front of Table to Center of Blade.....	17 in.
Distance Front of Table to Blade At Maximum Cut.....	12 in.
Main Table Size Thickness.....	1-3/4 in.

Fence Information

Fence Type.....	Camlock T-Shape w/HDPE Face (Shop Fox Classic)
Fence Size Length.....	42 in.
Fence Size Width.....	3-15/16 in.
Fence Size Height.....	2-1/2 in.
Fence Rail Type.....	Square Steel Tubing/Angle Iron
Fence Rail Length.....	47 in.
Fence Rail Width.....	4 in.
Fence Rail Height.....	3 in.

Miter Gauge Information

Miter Gauge Slot Type.....	T-Slot
Miter Gauge Slot Size Width.....	3/4 in.
Miter Gauge Slot Size Height.....	3/8 in.

Construction

Table.....	Precision-Ground Cast Iron
Wings.....	Precision-Ground Cast Iron
Cabinet.....	Pre-Formed Steel
Trunnions.....	Cast Iron
Fence Assembly.....	HDPE Plastic Side Panels, Heavy Walled Rectangular Steel Tubing Body
Rails.....	Steel
Miter Gauge Construction.....	Cast Iron
Guard.....	Steel and Clear Plastic
Body/Cabinet Paint Type/Finish.....	Powder Coated
Arbor Bearings.....	Sealed & Permanently Lubricated

Other Related Information

Number of Dust Ports.....	1
Dust Port Size.....	4 in.
Optional Long Rails.....	G9221
Max Rip Right of Blade w/Optional Long Rails.....	52 in.
Compatible Mobile Base.....	D2057A

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 1 Hour
Serial Number Location ID Label on Front of Stand, Above Grizzly Nameplate
ISO 9001 Factory No
Certified by a Nationally Recognized Testing Laboratory (NRTL) No
Awards Popular Woodworking Editors' Choice Buying Guide Tool, American Woodworker Editors' Choice 2002

Features:

Two Cast-Iron Extension Wings
All Sealed Ball Bearing Construction
Blade Guard
Extra-Large Handwheels
Heavy-Duty Miter Gauge
Magnetic Safety Switch Protects Motor and Operator
One Piece Steel Cabinet-Style Stand
Powder Coated Paint
Precision-Ground Cast-Iron Table with Beveled Edge
Shop Fox Classic Table Saw Fence
All Machined Cast-Iron Internal Structure
Two Table Inserts for Blade and Dado
Precision-Ground Cast-Iron Wings
Angled Dust Chute in Bottom of Stand
Clear Plastic Guard with Steel Splitter
Inboard and Outboard Arbor Bearings