



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

GRIZZLY MODEL G1066 DRUM SANDER

Design TypeFloor Model

Overall Dimensions:

Height43"
Width.....34½"
Depth.....37"
Belt Height.....31"
Shipping Weight.....430 lbs.
Net Weight389 lbs.
Crate Size39½" L x 41" W x 44" H
Footprint34½" x 24"

Capacities:

Maximum Board Width23½"
Maximum Board Thickness4¼"
Minimum Board Length9"
Minimum Board Thickness½"
Surface Speed of Drums2800 FPM
Conveyor Feed Rate11 FPM

Sanding Drum Motor:

TypeTEFC Capacitor Start Induction
Horsepower.....5 HP
Voltage220V ONLY
Amps.....25
RPM3450
Phase/CycleSingle/ 60 HZ
Power TransferBelt Drive

Conveyor Motor:

TypeTEFC Capacitor Start Induction
Horsepower¼ HP
Voltage220V
Amps.....3
RPM1720
Phase/CycleSingle/ 60 HZ
Power TransferChain Drive

General Construction:

FrameSteel
Sanding Drums (2)6" Diameter Aluminum
Pressure Rollers (3)1 ⅝" Diameter Rubber
Conveyor Belt24" x 74" Continuous Belt
.....Requires Sanding Rolls 6" Wide
.....2-4" Dust Ports Included
.....Cabinet Sheet Metal Powder Coated

Specifications, while deemed accurate, are not guaranteed.