



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

GRIZZLY MODEL G1258 20" BANDSAW

Design Type: Floor Model

Overall Dimensions:

Table20" W x 24"D x 1 $\frac{5}{8}$ " Thick
Overall Height75"
Height From Floor to Table35 $\frac{1}{4}$ "
Width38 $\frac{1}{2}$ "
Depth including Fence27 $\frac{3}{4}$ "
Shipping Weight613 lbs.
Weight in Place514 lbs.
Crate Size36" L x 25" W x 82" H
Footprint31" x 19 $\frac{1}{4}$ "

Cutting Capacity:

Left of Blade20"
Height14"
Table Tilt10° L, 45° R

Construction:

TablePrecision Ground Cast Iron
Upper WheelFully Balanced Cast Aluminum with Rubber Tires
Lower WheelFully Balanced Cast Iron with Rubber Tires
Rip FenceCast Iron
Wheel CoversPre-Formed Steel
GuidesAll Ball Bearing Guides

Motor:

TypeTEFC Capacitor Start Induction
Horsepower3 HP
Phase / CycleSingle Phase / 60 Hz
Voltage220V
Amps15
RPM1720
BearingsShielded & Permanently Lubricated Ball
SwitchMagnetic with Thermal Overload Protector

Blades:

Sizes AvailableFrom $\frac{3}{16}$ " to 1 $\frac{1}{4}$ "
Standard Blade Length154 $\frac{1}{2}$ "
Blade Speed3500 FPM

Features:

.....Micro-Adjustable Ball Bearing Blade Guides
.....Cast Iron Fence
.....Miter Gauge
.....4" Dust Port
.....Foot Brake
.....Rack & Pinion Upper Guide Adjustment

Specifications, while deemed accurate, are not guaranteed.