



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 • To Order Call: (800) 523-4777 • Fax #: (800) 438-5901

MODEL G3622/G3623/G3708/G4787/G4788 INDUSTRIAL BUFFER

Model Number	G3622	G3623	G3708	G4787	G4788
Motor	1 HP	2 HP	2 HP	3 HP	5 HP
Voltage	220V	220V	220V	220V	220V
Phase	Single-Phase	Single-Phase	3-Phase	3-Phase	3-Phase
Amps	8	14	6	9	9
Speed	1200 RPM	1200 RPM	1200 RPM	1200 RPM	900 RPM
Switch	Push Button	Push Button	Push Button	Push Button	Push Button
Type	TEFC Capacitor-Start Induction	TEFC Capacitor-Start Induction	TEFC Induction	TEFC Induction	TEFC Induction
Bearings	Shielded & Permanently Lubricated	Shielded & Permanently Lubricated	Shielded & Permanently Lubricated	Shielded & Permanently Lubricated	Shielded & Permanently Lubricated
Height	18¾"	21½"	21½"	21½"	21½"
Height (w/G4789 Stand)	46¾"	49½"	49½"	49½"	49½"
Width	38½"	41"	41"	45"	45"
Depth	7½"	9¼"	9¼"	9½"	8½"
Depth (w/G4789 Stand)	15¾"	15¾"	15¾"	15¾"	15¾"
Footprint Size	7"L x 9½"W	10¼"L x 8¼"W	10¼"L x 8¼"W	8¼"L x 10¼"W	10½"L x 8¼"W
Footprint Size (w/Stand)	17¾"L x 15¾"W	17¾"L x 15¾"W	17¾"L x 15¾"W	17¾"L x 15¾"W	17¾"L x 15¾"W
Net Weight	78 lbs	123 lbs.	116 lbs.	124 lbs.	128 lbs.
Shipping Weight	105 lbs	151lbs	143 lbs	153 lbs	164 lbs.
Crate Size	42"L x 10¼W x 15½"H	47¾"L x 12"W x 17¾"H	43½"L x 12"W x 17¾"H	48"L x 12"W x 17½"H	11½"L x 17"W x 47"H
Total Shaft Length	11¾"	11⅞"	11⅞"	13¾"	13¾"
Shaft Size w/Thread	8" x ⅞"	8" x 1¼"	8" x 1¼"	10" x 1¼"	8" x 1½"
Shaft Height From Base	7½"	9¼"	9¼"	9¼"	8¾"
Wrench Size	1⅝"(2)	1½"(1), 2"(1)	1½"(1), 2"(1)	1½"(1), 2"(1)	1½"(1), 2"(1)
Spacers	1"(4), 1½"(4), 2"(2)	1"(4), 1½"(4), 2"(2)	1"(4), 1½"(4), 2"(2)	1"(4), 1½"(4), 2"(4)	1"(4), 1½"(4), 2"(4)
Country of Origin	Taiwan	Taiwan	Taiwan	Taiwan	Taiwan
Assembly Time (approx.)	10 Minutes	10 Minutes	10 Minutes	10 Minutes	10 Minutes
Warranty	1 Year	1 Year	1 Year	1 Year	1 Year

