



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G9958 4 HP DUST COLLECTOR

Product Dimensions:

Weight..... 290 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 69 x 24 x 102 in.
Footprint (Length x Width)..... 69 x 24 in.

Shipping Dimensions:

Type..... Cardboard Box & Wood Frame
Content..... Machine
Weight..... 332 lbs.
Length x Width x Height..... 29 x 49 x 28 in.

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 32A
Minimum Circuit Size..... 40A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 10 ft.
Power Cord Gauge..... 12 AWG
Plug Included..... No
Switch Type..... Magnetic Switch w/Thermal Overload Protection

Motors:

Main

Horsepower..... 4 HP
Phase..... Single-Phase
Amps..... 32A
Speed..... 3450 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Direct Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Operation

Dust Collector Type..... Single-Stage
Approved Dust Types..... Wood
Filter Type..... Bag
Airflow Performance..... 3560 CFM
Max Static Pressure (at 0 CFM)..... 16.8 in.
Main Inlet Size..... 9 in.
Inlet Adapter Included..... Yes
Number of Adapter Inlets..... 4
Adapter Inlet Size..... 4 in.
Machine Collection Capacity At One Time..... 4
Maximum Material Collection Capacity..... 13.8 cu. ft.

Filter Information

Filtration Rating..... 1 Micron

Bag Information

Number of Upper Bags..... 2
Number of Lower Bags..... 2
Upper Bag Diameter..... 19-1/2 in.
Upper Bag Length..... 47 in.
Lower Bag Diameter..... 19-1/2 in.
Lower Bag Length..... 40 in.

Impeller Information

Impeller Type..... Radial Fin
Impeller Size..... 13 in.
Impeller Blade Thickness..... 3/32 in.

Construction

Upper Bag..... Fabric
Lower Bag..... Fabric
Base..... Steel Sheet Metal w/Casters
Frame..... Formed Steel
Caster..... High Density Plastic
Impeller..... Steel
Paint Type/Finish..... Powder Coated

Other Specifications:

Country of Origin Taiwan
Warranty 1 Year
Approximate Assembly & Setup Time 1 Hour
Serial Number Location ID Label
ISO 9001 Factory Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) No

Features:

Handles Four Machines Simultaneously
Convenient Caster Base Allows You to Move This Unit Easily
Includes Steel Base with Casters