



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G9982 OSCILLATING EDGE SANDER

Product Dimensions:

Weight..... 375 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 57 x 23-1/2 x 47 in.
Footprint (Length x Width)..... 32-1/2 x 18 in.

Shipping Dimensions:

Type..... Wood Slat Crate
Content..... Machine
Weight..... 428 lbs.
Length x Width x Height..... 0 x 0 x 0 in.

Electrical:

Power Requirement..... 220V, Single-Phase, 60 Hz
Prewired Voltage..... 220V
Full-Load Current Rating..... 14A
Minimum Circuit Size..... 20A
Plug Included..... No
Switch Type..... Magnetic Switch w/Thermal Overload Protection

Motors:

Main

Horsepower..... 2 HP
Phase..... Single-Phase
Amps..... 14A
Speed..... 1725 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Direct Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... External

Main Specifications:

Operation Information

Sanding Belt Speed..... 3500 FPM
Sanding Belt Oscillations..... 1/4 in.
Sanding Belt Length..... 108 in.
Sanding Belt Width..... 6 in.

Table Information

Table Length..... 40 in.
Table Width..... 11-1/2 in.
Table Thickness..... 2 in.
Table Tilt..... 0 – 45 deg.
Table Travel..... 6 in.
Floor To Table Height..... 33 in.

Platen Information

Platen Type..... Graphite Coated
Platen Length..... 35 in.
Platen Width..... 8 in.

Construction

Table.....	Stainless Steel
Frame.....	Steel
Base.....	Steel
Drive Roller.....	Aluminum
Idler Roller.....	Rubber
Paint Type/Finish.....	Powder Coated

Other Related Information

Number of Dust Ports.....	1
Dust Port Size.....	5 in.
Belt Release.....	Quick Release
Drive Roller Size.....	7-7/8 in.
Idler Roller Size.....	7-7/8 in.

Other Specifications:

Country of Origin	Taiwan
Warranty	1 Year
Serial Number Location	ID Label on Right Door of Stand
ISO 9001 Factory	No
Certified by a Nationally Recognized Testing Laboratory (NRTL)	No

Features:

- Miter Work Stop
- Quick Belt Release
- Conveniently Located Belt Tracking and Tension Adjustment
- Powder Coated Finish
- Stainless Steel Table
- 1/4" Belt Oscillation
- Top-Mounted Magnetic Switch
- Spring Adjusted Table for Easy Movement