



ENGINEERING & TECHNICAL DATA

© Grizzly Industrial, Inc. • Customer Service: (800) 523-4777 • Tech Support: (570) 546-9663

HEAVY-DUTY WIRE-REINFORCED HOSE

Model	Inside Diameter (Inches)	Length (Feet)	Approx. Weight (Lbs/Ft)	Wall Thickness (Inches)	Bend Radius (Inches)	Compression Ratio	Negative Pressure (In/Hg)	Working Pressure (PSI)
H6953	9	2	1.36	0.028	9	3:1	2.5	7
H6954	9	10	1.65	0.028	9	4:1	1.1	7
H7462	7	3	0.98	0.028	7	3:1	5	9
H7463	7	10	0.98	0.028	7	3:1	5	9
H7464	8	3	1.13	0.028	8	3:1	3.5	8
H7465	8	10	1.13	0.028	8	3:1	3.5	8
W1034	4	10	0.55	0.025	3.7	4:1	18	13
W1035	5	10	0.67	0.025	5	4:1	9	12
W1036	6	10	0.90	0.028	6	3:1	8	11

(Technical data based on 2-foot straight lengths of hose at 72°F)

Construction: Medium-weight PVC hose re-inforced with a spring-steel wire helix

Temperature Range: 20°F–160°F

Color: Clear