



Product Specifications

P.O. Box 2027, Bellingham, WA 98227 U.S.A.
PHONE: (360) 734-1540 • © South Bend Tools
www.southbendtools.com



Model SB1018 5" X 6" Horizontal Bandsaw

Product Dimensions

Weight.....	209 lbs.
Width (side-to-side) x Depth (front-to-back) x Height.....	38-3/4 x 17 x 42-1/4 in.
Footprint (Length x Width).....	38-3/4 x 17 in.
Space Required for Full Range of Movement (Width x Depth).....	41-1/8 x 29-7/16 in.

Shipping Dimensions

Type.....	Cardboard Box on Wood Skids
Content.....	Machine
Weight.....	216 lbs.
Length x Width x Height.....	41 x 19 x 24 in.

Electrical

Power Requirement.....	110V or 220V, Single-Phase, 60 Hz
Prewired Voltage.....	110V
Full-Load Current Rating.....	8.6A at 110V, 4.3A at 220V
Minimum Circuit Size.....	15A at 110V, 15A at 220V
Connection Type.....	Cord & Plug
Power Cord Included.....	Yes
Power Cord Length.....	7 ft.
Power Cord Gauge.....	18 AWG
Plug Included.....	Yes
Included Plug Type.....	5-15 for 110V
Recommended Plug Type.....	6-15 for 220V
Switch Type.....	Push Button ON/OFF Switch
Voltage Conversion Kit.....	PSB1018204 for 220V

Motors

Main

Horsepower.....	1/2 HP
Phase.....	Single-Phase
Amps.....	8.6A/4.3A
Speed.....	1725 RPM
Type.....	TEFC Capacitor-Start Induction
Power Transfer	V-Belt Drive
Bearings.....	Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type.....	External

Main Specifications

Operation Info

Blade Speeds.....	80, 120, 200 FPM
Std. Blade Length.....	64-1/2 in.
Blade Length Range.....	1/2 in.
Head Swivel.....	60 deg.

Cutting Capacities

Angle Cuts.....	60 deg.
Vise Jaw Depth.....	7-7/8 in.
Vise Jaw Height.....	2-1/2 in.
Max. Capacity Rectangular Height at 90 Deg.....	5 in.
Max. Capacity Rectangular Width at 90 Deg.....	6 in.
Max. Capacity Round at 90 Deg.....	5 in.
Max. Capacity Rectangular Height at 45 Deg.....	2-5/16 in.
Max. Capacity Rectangular Width at 45 Deg.....	3-3/4 in.
Max. Capacity Round at 45 Deg.....	3-3/4 in.
Max. Capacity Rectangular Height at 60 Deg.....	1-1/2 in.
Max. Capacity Rectangular Width at 60 Deg.....	2-3/16 in.
Max. Capacity Round at 60 Deg.....	1-1/2 in.

Construction

Upper Wheel.....	Cast Iron
Lower Wheel.....	Cast Iron
Tire.....	Rubber
Body.....	Cast Iron
Base.....	Cast Iron
Stand.....	Steel

Other

Wheel Size.....	5 in.
Blade Guides Upper.....	Yes
Blade Guides Lower.....	Yes

Table Info

Floor To Cutting Area Height.....	28-1/8 in.
-----------------------------------	------------

Other

Country of Origin	Taiwan
Warranty	2 Years
Approximate Assembly & Setup Time	1 Hour
Serial Number Location	ID Label on Body Frame
ISO 9001 Factory	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL)	No

Features

- Heavy-Duty Steel Stand
- Adjustable Hydraulic Down Feed
- Cast-Iron Handwheel with Chromed Handle
- Die Cast South Bend Star Knobs
- Die Cast South Bend Belt Guard
- Built-In Storage Cabinet
- Leveling Feet and Wheels to Ease Mobility
- Swiveling Head
- Precision-Ground Vise Deck and Table