



Product Specifications

P.O. Box 2027, Bellingham, WA 98227 U.S.A.
PHONE: (360) 734-1540 • © South Bend Tools
www.southbendtools.com



Model SB1024F 9" x 42" 2 HP Mill with DRO

Product Dimensions

Weight.....	1984 lbs.
Width (side-to-side) x Depth (front-to-back) x Height.....	63 x 58 x 87 in.
Footprint (Length x Width).....	36 x 24 in.
Space Required for Full Range of Movement (Width x Depth).....	81-1/2 x 66 in.

Shipping Dimensions

Type.....	Wood Crate
Content.....	Machine
Weight.....	2130 lbs.
Length x Width x Height.....	54 x 54 x 73 in.

Electrical

Power Requirement.....	220V, Single-Phase, 60 Hz
Prewired Voltage.....	220V
Full-Load Current Rating.....	14A
Minimum Circuit Size.....	20A
Connection Type.....	Cord & Plug
Power Cord Included.....	No
Recommended Power Cord.....	"S"-Type, 3-Wire, 14 AWG, 300 VAC
Plug Included.....	No
Recommended Plug Type.....	6-20
Switch Type.....	Control Panel w/Magnetic Switch Protection

Motors

Main

Horsepower.....	2 HP
Phase.....	Single-Phase
Amps.....	14A
Speed.....	1720 RPM
Type.....	AEVF Capacitor-Start Induction
Power Transfer	Belt Drive
Bearings.....	Sealed & Permanently Lubricated
Centrifugal Switch/Contacts Type.....	External

Main Specifications

Operation Info

Spindle Travel.....	5 in.
Max Distance Spindle to Column.....	19 in.
Max Distance Spindle to Table.....	19 in.
Longitudinal Table Travel (X-Axis).....	23-1/2 in. (29-1/2 in. w/o Power Feed)
Cross Table Travel (Y-Axis).....	13 in.
Vertical Table Travel (Z-Axis).....	16 in.
Ram Travel.....	13 in.
Turret or Column Swivel (Left/Right).....	360 deg.
Head Tilt (Left/Right).....	90 deg.
Head Tilt (Front/Back).....	45 deg.
Drilling Capacity for Cast Iron.....	1 in.
Drilling Capacity for Steel.....	3/4 in.
End Milling Capacity.....	1 in.
Face Milling Capacity.....	4 in.

Table Info

Table Length.....	42 in.
Table Width.....	9 in.
Table Thickness.....	3 in.
Number of T-Slots.....	3
T-Slot Size.....	5/8 in.
T-Slots Centers.....	2-1/2 in.
Number of Longitudinal Feeds.....	Variable
X-Axis Table Power Feed Rate.....	0 – 3.34 FPM
X/Y-Axis Travel per Handwheel Revolution.....	0.200 in.
Z-Axis Travel per Handwheel Revolution.....	0.100 in.

Spindle Info

Spindle Taper.....	R-8
Number of Vertical Spindle Speeds.....	Variable
Range of Vertical Spindle Speeds.....	60 – 4200 RPM
Quill Diameter.....	3.375 in.
Quill Feed Rates.....	0.0015, 0.003, 0.006 in./rev.
Drawbar Thread Size.....	7/16-20
Drawbar Length.....	18-1/2 in.
Spindle Bearings.....	Angular Contact P4 (ABEC-7) & Double-Shielded Ball Bearing

Construction

Spindle Housing/Quill.....	Chrome-Plated & Precision-Ground Steel
Table.....	Hardened & Precision-Ground Cast Iron
Head.....	Meehanite Cast Iron
Column/Base.....	Meehanite Cast Iron
Base.....	Cast Iron
Paint Type/Finish.....	Urethane

Other

Country of Origin	Taiwan
Warranty	2 Years
Approximate Assembly & Setup Time	1 Hour
Serial Number Location	ID Label on Column Right Side
Sound Rating	55 dB

Features

Fagor DRO
High-Quality, Low-Vibration AEVF Spindle Motor
P4 (ABEC-7) High-Quality Angular Contact Spindle Bearings
X & Y Leadscrew Nuts Double-Bronzed for Ultra-Smooth Movement w/Minimal Backlash
Lever-Action, One-Shot Pump Lubrication System
Auto-Downfeed Stop with Micro-Adjustable Stop
Variable Speed Longitudinal Power Feed
Hardened and Precision-Ground Table Surface
Chromed Steel Quill
Heavy-Duty Spindle Brake
Halogen Work Light
Allen-Bradley Electrical Controls
Japanese NSK/NTN Bearings
Table, Knee and Ram are Equipped with Dual Locking Mechanisms
Turcite Coated Ways
South Bend Brass Nameplate
Meehanite Castings
Typical South Bend "No Compromises" Fashion