



MACHINE DATA SHEET

© Grizzly Industrial, Inc. • Customer Service: (800) 523-4777 • Tech Support: (570) 546-9663

MODEL T10687 TRACK SAW

Product Dimensions:

Weight 11 lbs.
Width (side-to-side)/Depth (front-to-back)/Height 13³/₈" x 10¹/₄" x 9¹/₂"

Shipping Dimensions:

Type Cardboard Box
Content..... Machine
Weight..... 16 lbs.
Width/Depth/Height 13" x 10⁵/₈" x 9¹/₄"

Electrical:

Switch..... Trigger with Safety Latch
Cord Length 6 ft.
Cord Gauge 18 AWG
Plug Type Included NEMA 1-15 Two-Prong Polarized

Motor:

Type Universal
Horsepower..... 1.1 KW
Voltage..... 120V
Phase..... Single-Phase
Amps..... 9A
Speed..... 5500 RPM
Cycle 60 Hz

Main Specifications:

Blade Specifications

Blade Diameter..... 160mm (6¹/₄")
Blade Tilt 0°-45°
Arbor Size..... 20mm
Arbor Speed 5500 RPM
Blade Rim Speed 9070 FPM

Cutting Capacities

Maximum Depth of Cut at 90° (without rail track) 2⁵/₃₂"
Maximum Depth of Cut at 45° (without rail track) 1⁵/₈"
Maximum Depth of Cut at 90° (with rail track) 1³¹/₃₂"
Maximum Depth of Cut at 45° (with rail track) 1⁷/₁₆"

Construction

Saw Construction Aluminum and Engineered Plastic
Hand Grips Heavy-Duty Rubberized
Rail Track Aluminium
Number of Dust Ports..... 1
Dust Port Size 1¹/₂"

Other Specifications:

Country Of Origin China
Warranty..... 1 Year
Serial Number LocationID Label on Motor Housing
Assembly Time 10 Minutes

Features:

Anti-Kickback Design with Spring-Loaded Riving Knife
Low-Profile Blade Guard for Cuts as Close as 5/8" from Wall
1 1/2" Dust Port for Efficient Dust Collection
Versatile—Saw can be Used With or Without Track
Precision Depth Control Scale in 1/32" Increments
48 Tooth Carbide Tip Blade Included

Optional Accessories:

T24872 55" Rail Track
T25094 Accessories Pack (Includes rail connector, (2) F-clamps, stop, and stabilizer)
T25331 48-Tooth Replacement Blade