



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL T28360 7" OVERHEAD WET-CUTTING TILE SAW

Product Dimensions:

Weight 44 lbs.
Width (side-to-side) x Depth (front-to-back) x Height 35 x 18 x 14 in.
Footprint (length x width) 19-1/2 x 15-3/4 in.

Shipping Dimensions:

Type Cardboard Box
Content..... Machine
Weight..... 49 lbs.
Length x Width x Height..... 37 x 21 x 14 in.
Must Ship Upright Yes

Electrical:

Power Requirement 120V, Single-Phase, 60 Hz
Full-Load Current Rating..... 6.64A
Minimum Circuit Size 15A
Connection Type Cord & Plug
Power Cord Included Yes
Power Cord Length 6 ft.
Power Cord Gauge 18 AWG
Plug Included Yes
Included Plug Type 5-15P
Switch Type..... ON/OFF Toggle Switch

Motors:

Main

Type..... TEFC Capacitor Run Induction
Horsepower 1 HP
Voltage..... 120V
Phase Single-Phase
Amps 6.5A
Speed 3450 RPM
Cycle..... 60 Hz
Power Transfer Direct Drive
Bearings Sealed & Permanently Lubricated

Coolant Pump

Type..... Universal
Horsepower 17 Watts
Voltage..... 120V
Phase Single-Phase
Amps 0.14A
Cycle..... 60 Hz

Specifications:**Operation Information**

Arbor Diameter	5/8 in.
Maximum Blade Diameter	7 in.
Head & Track Tilt	45° Left-Tilt
Maximum Cut Length (w/Fence)	18 in.
Maximum Cutting Thickness @ 90°	1-1/4 in.
Maximum Cutting Thickness @ 45°	1-1/4 in.
Coolant Pump	27 GPH

Construction

Frame	Steel
Tub	Plastic
Table	Aluminum
Paint Type/Finish	Powder Coated

Other Specifications:

Country of Origin	Taiwan
Warranty	1 Year
Approximate Assembly & Setup Time	15 min.
Serial Number Location	ID Label
ISO 9001 Factory	Yes

Features:

Miter Gauge
Ultra-Quiet Induction Motor
Smooth-Sliding Dual Rails
Water Pump Capacity of 27 Gallons Per Hour
Workpiece Back-Stop Clamping Plate on Table
7" Saw Blade
Comfortable Rubber Grip Handle
Drain Plug in Tub
Head and Track Tilt to 45° Left for Beveled Cuts

Accessories Include:

Miter Gauge
Workpiece Clamp
7" Saw Blade