



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL T32336 4-GALLON OIL-FREE QUIET AIR COMPRESSOR

Product Dimensions:

Weight 60 lbs.
Width (side-to-side) x Depth (front-to-back) x Height 19 x 17 x 20 in.
Footprint (Length x Width) 15 x 12-1/2 in.

Shipping Dimensions:

Type Cardboard Box
Content Machine
Weight 62 lbs.
Length x Width x Height 23 x 17 x 20 in.

Electrical:

Power Requirement 110V, Single-Phase, 60 Hz
Full-Load Current Rating 13A
Minimum Circuit Size 20A
Connection Type Cord & Plug
Power Cord Included Yes
Power Cord Length 72 in.
Power Cord Gauge 14 AWG
Plug Included Yes
Included Plug Type 5-15
Switch Type Pressure Switch w/Circuit Breaker

Motor:

Main

Horsepower 2 HP
Phase Single-Phase
Amps 13A
Speed 1725 RPM
Type Induction
Power Transfer Direct
Bearings Shielded & Permanently Lubricated

Main Specifications:

Operation Information

Compressor Style Horizontal
Pump Type One-Stage
Max. Airflow/Delivery (at 40 PSI) 6.2 SCFM
Max. Airflow/Delivery (at 90 PSI) 5.6 SCFM
Cut-Out Pressure 125 PSI
Cut-In Pressure 95 PSI
Duty Cycle 50/50
Tank Size 4 Gallons (Twin Stack)
Number of Cylinders 2
Pump Lubrication Oil-Free
Drain Valve Type Ball-Valve
Roll Cage Yes
Regulator Yes

Output Port Information

Connection Type Quick-Coupler
Connection Size 1/4" NPT
Number of Connections 2
Hose Included No

Construction Information

Tank Steel
Valves Brass-Coated
Cage/Frame Steel
Paint Type/Finish Enamel

Other Specifications:

Country of Origin China
Warranty 1 Year
Serial Number Location ID Label
Sound Rating 60-71 dB

Features:

- Sound Rating of Under 71 dB
- Oil-Free Lubrication
- 4-Gallon Twin-Stack with Maximum Airflow of 5.6 SCFM at 90 PSI
- Ball-Valve Drain Control
- Durable Roll Cage with Rubber Feet for Protected Portability
- Included Air Regulator for Airflow Adjustment
- Two Quick-Coupler Hose Connections