



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL T32339 20-GALLON 2 HP PORTABLE AIR COMPRESSOR

Product Dimensions:

Weight 183 lbs.
Width (side-to-side) x Depth (front-to-back) x Height 24 x 23 x 44 in.
Footprint (Length x Width) 21 x 14-1/2 in.

Shipping Dimensions:

Type Cardboard Box
Content Machine
Weight 215 lbs.
Length x Width x Height 24 x 31 x 47 in.

Electrical:

Power Requirement 115V or 230V, Single-Phase, 60 Hz
Prewired Voltage 115V
Full-Load Current Rating 15A at 115V, 7.5A at 230V
Minimum Circuit Size 20A at 115V, 15A at 230V
Connection Type Cord & Plug
Power Cord Included Yes
Power Cord Length 72 in.
Power Cord Gauge 12 AWG
Plug Included Yes
Included Plug Type 5-15
Recommended Plug Type 6-15 for 230V
Switch Type Pressure Switch w/Motor Reset Button

Motors:

Main

Horsepower 2 HP
Phase Single-Phase
Amps 15A at 115V, 7.5A at 230V
Speed 3450 RPM
Type ODP Capacitor-Start
Power Transfer Belt
Bearings Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type External

Main Specifications:

Operation Information

Compressor Style Vertical
Pump Type One-Stage
Max. Airflow/Delivery (at 40 PSI) 7 SCFM
Max. Airflow/Delivery (at 90 PSI) 6 SCFM
Cut-Out Pressure 125 PSI
Cut-In Pressure 95 PSI
Duty Cycle 50/50
Tank Size 20 Gallons
Number of Cylinders 2
Pump Lubrication Grizzly Model T28041 or Equivalent Air Compressor Oil
Drain Valve Type Ball Valve
Regulator Yes

Output Port Information

Connection Type Quick-Coupler
Connection Size 1/4" NPT
Number of Connections 1
Hose Included No

Construction Information

Tank Steel
Valves Brass-Coated
Paint Type/Finish Enamel

Other Specifications:

Country of Origin USA
Warranty 1 Year
Serial Number Location ID Label

Features:

- 20-Gallon Tank with Maximum Airflow of 6 SCFM at 90 PSI
- Ball-Valve Drain Control
- No-Flat Wheels and Feet for Portability
- Included Air Regulator for Airflow Adjustment
- Quick-Coupler Hose Connection