



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL T33256 4" X 36" BELT / 6" DISC COMBO SANDER

Product Dimensions:

Weight..... 33 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 20 x 16-1/2 x 25 in.
Footprint (Length x Width)..... 16-1/2 x 10 in.

Shipping Dimensions:

Type..... Cardboard
Content..... Machine
Weight..... 36 lbs.
Length x Width x Height..... 22 x 13 x 16 in.
Must Ship Upright..... Yes

Electrical:

Power Requirement..... 120V, Single-Phase, 60Hz
Full-Load Current Rating..... 4.3A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 74 in.
Power Cord Gauge..... 18 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Paddle Safety Switch w/ Removable Key

Motors:

Main

Horsepower..... 1/2 HP
Phase..... Single-Phase
Amps..... 4.3A
Speed..... 1700 RPM
Type..... Induction
Power Transfer Belt
Bearings..... Sealed & Permanently Lubricated

Main Specifications:

Belt Sander Info

Sanding Belt Width.....	4 in.
Sanding Belt Length.....	36 in.
Sanding Belt Speed.....	1320 FPM
Sanding Belt Tilt.....	0-90 deg.
Table-to-Floor Height.....	12-5/8 in.
Max Height of Belt in Vertical Position.....	24-5/8 in.
Contact Wheel Diameter.....	2-1/4 in.
Contact Wheel Width.....	4 in.
Drive Wheel Diameter.....	2-1/4 in.
Drive Wheel Width.....	4 in.
Belt Tension Release Type.....	Quick-Release Lever
Platen Type.....	Steel
Platen Length.....	11-1/2 in.
Platen Width.....	4-3/4 in.

Disc Sander Info

Disc Diameter.....	6 in.
Disc Speed.....	2200 RPM
Disc Sandpaper Backing Type.....	PSA
Table Length.....	7 in.
Table Width.....	5-3/8 in.
Table Thickness.....	5/8 in.
Table Tilt.....	0-45 deg.
Table-to-Floor Height.....	9-1/8 in.

Construction Materials

Base.....	Cast Aluminum
Table.....	Cast Aluminum
Frame.....	Steel
Disc.....	Aluminum
Miter Gauge.....	Plastic
Paint Type/Finish.....	Urethane

Other Related Info

Miter Gauge Slot Width.....	5/8 in.
Miter Gauge Slot Height.....	1/4 in.
Number of Dust Ports.....	1
Dust Port Size.....	2 in.

Other Specifications:

Country of Origin	China
Warranty	1 Year
Approximate Assembly & Setup Time	15 Minutes
ISO 9001 Factory	Yes

Features:

- 0-90 Degree Belt Tilt
- 0-45 Degree Table Tilt for Use with Disc or Platen
- Work Stop
- Adjustable Miter Gauge
- 6" 80-Grit Abrasive Disc Included
- 4" x 36" 80-Grit Sanding Belt Included
- Cord Storage Brackets
- Quick-Release Belt Tension Lever
- Single-Nut Tracking Adjustment