



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL T34359 20" X 37" METALWORKING DOWNDRAFT TABLE

Product Dimensions:

Weight..... 220 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 41-1/2 x 24-1/2 x 33-1/2 in.
Footprint (Length x Width)..... 39-1/2 x 20 in.

Shipping Dimensions:

Type..... Cardboard Box on Wood Pallet
Content..... Machine
Weight..... 251 lbs.
Length x Width x Height..... 43 x 29 x 34 in.

Electrical:

Power Requirement..... 110V, Single-Phase, 60 Hz
Full-Load Current Rating..... 6A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 72 in.
Power Cord Gauge..... 14 AWG
Plug Included..... Yes
Included Plug Type..... 5-15
Switch Type..... Paddle Safety Switch w/Removable Key

Motors:

Main

Horsepower..... 3/4 HP
Phase..... Single-Phase
Amps..... 6A
Speed..... 1150 RPM
Type..... TENV Capacitor-Start Induction
Power Transfer Direct
Bearings..... Shielded & Permanently Lubricated

Main Specifications:

Operation Info

Air Suction Capacity..... 1850 CFM
Filter Micron..... 200
Filter Efficiency..... 90%
Impeller Type..... Squirrel Cage
Impeller Size..... 9-1/2 x 7 in.
Inlet Hole Diameter..... 8 in.
Outlet Size..... 10 x 8 in.

Filter Info

Number of Filters.....	2
Filter Length.....	20 in.
Filter Width.....	16 in.
Filter Thickness.....	1 in.

Table Info

Table Size Length.....	36-1/2 in.
Table Size Width.....	19-1/2 in.
Floor to Table Height.....	29-1/2 in.
Table Load Capacity.....	440 lbs.

Construction Info

Frame.....	Steel
Impeller.....	Steel
Table.....	Steel
Paint Type/Finish.....	Powder Coated

Other Specifications:

Country of Origin	Taiwan
Warranty	1 Year
Approximate Assembly & Setup Time	10 Min.
Serial Number Location	ID Label
Sound Rating	70 dB

Features:

- Designed to Accommodate Metal Sanding, Grinding, Soldering, and Polishing Applications
- 9-1/2" x 7" Squirrel Cage Fan
- Durable Powder-Coated Finish
- Quiet Operation
- Adjustable, Vibration-Dampening Rubber Feet
- 440 lb. Table Load Capacity