

MACHINE SPECIFICATIONS



© Woodstock International, Inc. • Phone #: (360) 734-3482 • Web: www.shopfox.biz

MODEL W1815 15" DISC SANDER w/BRAKE

Electrical

Required Power Source 220V, 1-Phase, 60 Hz
Switch Paddle Switch w/Disabling Key
Switch Voltage 220V
Cord Length..... 6 ft.
Cord Gauge 14 AWG
Minimum Circuit Size..... 15A
Plug Included Yes
Included Plug Type NEMA 6-15

Motor

Type TEFC Capacitor Start w/Brake
Horsepower 1½ HP
Voltage 220V
Phase..... Single
Amps 12A
Speed 1725 RPM
Cycle 60 Hz
Number Of Speeds..... 1
Power Transfer Direct Drive
Bearings Sealed, Permanently Lubricated

Main Specifications

Table & Disc Specifications

Table Tilt Range +15° to -45°
Sanding Disc Diameter..... 15"
Sanding Disc Speed..... 1725 RPM
Disc Table Length 20"
Disc Table Width..... 12"
Disc Table Thickness 9/16"
Miter Gauge Slot Width 3/4"
Miter Gauge Slot Height..... 5/16"
Floor to Table Height 37"

Overall Dimensions

Weight 201 lbs.
Length 20½"
Width 26"
Height 46"
Foot Print (Length/Width)..... 20½" x 26"

Shipping Dimensions

Carton 1

Type	Carboard
Content	Machine
Weight.....	138 lbs.
Length.....	25"
Width.....	22"
Height.....	20"

Carton 2

Type	Carboard
Content	Cabinet Stand
Weight.....	56 lbs.
Length.....	29"
Width.....	23"
Height.....	11"

Construction Materials

Base	Steel
Disc.....	Cast Iron
Miter Gauge.....	Aluminum
Cabinet Stand	Steel
Table	Precision Ground Cast Iron
Paint	Powder Coated

Other

Number of Dust Ports	1
Dust Port Size	2 1/2"
Customer Cleaning and Setup Time.....	Approximately 30 Minutes
Made in ISO 9001 Factory	Yes
Warranty	2 Year
Country of Origin	Taiwan
Serial Number Location.....	ID Label on Cabinet
Sound Rating.....	75 dB

Features

Automatic Internal Motor Braking System
Table Tilt Range +15° to -45°
Accepts 15" PSA Discs
Large Tilting Precision-Ground Cast Iron Table
X and Y-Axis Miter Slots
Steel Base