

MACHINE SPECIFICATIONS



© Grizzly Industrial, Inc. • Phone #: (360) 647-0802 • Web: www.shopfoxtools.com

MODEL W1846 1/4 HP BENCHTOP OSCILLATING SPINDLE SANDER

Product Dimensions

Weight..... 46 lbs.
Width (side-to-side) x Depth (front-to-back) x Height..... 23 x 18 x 20 in.
Footprint (Length x Width)..... 22-1/2 x 17 in.

Shipping Dimensions

Type..... Cardboard
Content..... Machine
Weight..... 56 lbs.
Length x Width x Height..... 25 x 20 x 22 in.

Electrical

Power Requirement..... 120V, Single-Phase, 60 Hz
Full-Load Current Rating..... 2.6A
Minimum Circuit Size..... 15A
Connection Type..... Cord & Plug
Power Cord Included..... Yes
Power Cord Length..... 6 ft.
Power Cord Gauge..... 18 AWG
Plug Included..... Yes
Included Plug Type..... NEMA 5-15
Switch Type..... Paddle Safety Switch w/Removable Key

Motors

Main

Horsepower..... 1/4 HP
Phase..... Single-Phase
Amps..... 2.6A
Speed..... 1725 RPM
Type..... TEFC Capacitor-Start Induction
Power Transfer Direct Drive
Bearings..... Shielded & Permanently Lubricated
Centrifugal Switch/Contacts Type..... N/A

Main Specifications

Spindle Sander Info

Sanding Drum Diameters.....	3/4, 1, 1-1/2, 2, 3 in.
Sanding Drum Length.....	4-1/2 in.
Spindle Oscillation.....	30 SPM
Stroke Length.....	1 in.
Table Length.....	18 in.
Table Width.....	18 in.
Table Thickness.....	11/16 in.
Spindle Shaft Diameter.....	1/2 in.
Number of Table Inserts.....	6

Other Related Info

Number of Dust Ports.....	1
Dust Port Size.....	2 in.

Other

Country of Origin	China
Warranty	2 Years
Serial Number Location	Machine ID Label on Front of Machine

Features

- A Spacious 18-inch Table Leaves Plenty of Room to Navigate While Smoothing Curved Edges.
- Sanding Drums Store Neatly in the Base for Easy, Organized Access.
- Space-Saving Benchtop Style.
- ON/OFF Paddle Switch with Removable Key.
- Includes 6 Sanding Sleeves from 1/2" to 3" in Diameter.