

# MACHINE SPECIFICATIONS



© Woodstock International, Inc. • Phone #: (800) 840-8420 • Web: [www.woodstockint.com](http://www.woodstockint.com)

## MODEL W1877 13" PORTABLE PLANER WITH SPIRAL-STYLE CUTTERHEAD

### Product Dimensions

Weight.....	84 lbs.
Width (side-to-side) x Depth (front-to-back) x Height.....	30 x 34 x 20 in.
Footprint (Length x Width).....	22 x 13-1/2 in.

### Shipping Dimensions

Type.....	Cardboard
Content.....	Machine
Weight.....	88 lbs.
Length x Width x Height.....	27 x 16 x 24 in.
Must Ship Upright.....	Yes

### Electrical

Power Requirement.....	120V, Single-Phase, 60 Hz
Full-Load Current Rating.....	15A
Minimum Circuit Size.....	20A
Connection Type.....	Cord & Plug
Power Cord Included.....	Yes
Power Cord Length.....	6 ft.
Power Cord Gauge.....	14 AWG
Plug Included.....	Yes
Included Plug Type.....	5-15
Switch Type.....	Paddle Safety Switch w/Removable Key

### Motors

#### Main

Horsepower.....	2 HP
Phase.....	Single-Phase
Amps.....	15A
Speed.....	20,000 RPM
Type.....	Universal
Power Transfer .....	Belt Drive
Bearings.....	Shielded & Permanently Lubricated

## Main Specifications

### Main Specifications

Planer Size.....	13 in.
Max. Cut Width.....	13 in.
Min. Stock Length.....	8 in.
Min. Stock Thickness.....	1/8 in.
Max. Stock Thickness.....	6 in.
Number of Cuts Per Inch.....	32
Number of Cuts Per Minute.....	60,000 (effective)
Cutterhead Speed.....	10,000 RPM
Planing Feed Rate.....	26 FPM
Max. Cut Depth Planing Full Width.....	1/16 in.
Max. Cut Depth Planing 6-Inch Wide Board.....	1/8 in.

### Cutterhead Info

Cutterhead Type.....	Spiral-Style
Cutterhead Diameter .....	2 in.
Number of Cutter Rows.....	6
Number of Indexable Cutters.....	26
Cutter Insert Type.....	HSS
Cutter Insert Size Length.....	14mm
Cutter Insert Size Width.....	14mm
Cutter Insert Size Thickness.....	2mm

### Table Info

Table/Headstock Movement.....	6 in.
Table Bed Size Length.....	9-1/4 in.
Table Bed Size Width.....	13 in.
Table Wings Size Length.....	12 in.
Table Wings Size Width.....	14 in.

### Construction

Table.....	Stainless Steel
Body.....	Plastic
Cutterhead Assembly.....	Steel
Infeed Roller.....	Rubber
Outfeed Roller.....	Rubber
Paint Type/Finish.....	Urethane

### Other

Table/Headstock Locks.....	Yes
Measurement Scale.....	Inch & Metric
Number of Dust Ports.....	1
Dust Port Size.....	4 in.

### Other

Country of Origin .....	Taiwan
Warranty .....	2 Years
Approximate Assembly & Setup Time .....	15 Min.
Serial Number Location .....	Machine ID Label
Sound Rating .....	96 - 98 dB
ISO 9001 Factory .....	Yes
Certified by a Nationally Recognized Testing Laboratory (NRTL) .....	Yes

## **Features**

- Spiral-Style Cutterhead with 26 Indexable HSS Inserts
- Stepped Depth-of-Cut Gauge: 1/8" - 1-3/4"
- Stock Thickness Scale: 0" - 6"
- Built-In Dust Collection with 4" Dust Port & 2-1/2" Adapter
- Enclosed Tool Storage
- Stainless Steel Table with Folding Extensions